



HIGH PRESSURE DIAPHRAGM PUMPS





APS 51

3 Diaphragm



Suction
 Ø 35

Delivery
 1 x Ø10
 1 x G 3/4" F



AVAILABLE MODELS

APS 51

6 Hole Flange



APS 51 MF

6 Hole Flange
 1 3/8" Male 6 Splined Shaft



APS 51 GR5

3/4" Hollow Shaft Gearbox
 Adjustable Regulator
 1/2" Outlet, 1" Bypass



APS 51 GR8

1" Hollow Shaft Gearbox
 Adjustable Regulator
 1/2" Outlet, 1" Bypass



ACCESSORIES & REPAIR KITS

Comet Oil



8102.1801.00

GCP 3V Regulators



1204.0680.00 (350 PSI)
 1204.0678.00 (580 PSI)

Hydraulic Flange



5011.0182.00

Shaft Protector



2416.0238.00

Rebuild Kits



NBR: 5026.0084.00
 Desmopan: 5026.0084.00.DS

		0 bar - 0 p.s.i.				20 bar - 290 p.s.i.				30 bar - 435 p.s.i.				40 bar - 580 p.s.i.					
RPM	l/min	U.S.g.p.m.	HP	kW	l/min	U.S.g.p.m.	HP	kW	l/min	U.S.g.p.m.	HP	kW	l/min	U.S.g.p.m.	HP	kW	kg	lb	
400	39.5	10.4	0.4	0.3	38.6	10.2	2.2	1.6	38.2	10.1	3.1	2.3	36.5	9.6	3.8	2.8	16.4	36.2	
450	44.4	11.7	0.5	0.4	43.4	11.5	2.5	1.8	43.0	11.4	3.4	2.5	41.1	10.9	4.2	3.1			
500	49.0	12.9	0.5	0.4	47.7	12.6	2.7	2.0	47.1	12.4	3.8	2.8	46.1	12.2	4.8	3.5			
550	53.9	14.2	0.6	0.4	52.4	13.8	3.0	2.2	51.8	13.7	4.2	3.1	50.7	13.4	5.2	3.8			