



HIGH PRESSURE DIAPHRAGM PUMPS





# APS 71

3 Diaphragm



Suction  
 Ø 35

Delivery  
 1 x Ø 10  
 1 x G 3/4" F



## AVAILABLE MODELS

**APS 71**  
6 Hole Flange

**APS 71 MF**  
6 Hole Flange  
1 3/8" Male 6 Splined Shaft

**APS 71 MM**  
1 3/8" Male 6 Splined Shaft  
on Both Sides

**APS 71 GR8**  
1" Hollow Shaft Gearbox  
Adjustable Regulator  
1/2" Outlet, 1" Bypass



## ACCESSORIES & REPAIR KITS

Comet Oil

GCP V3 Regulators

Hydraulic Flange

Shaft Protector

Rebuild Kits



8102.1801.00



1204.0680.00 (350 PSI)  
1204.0678.00 (580 PSI)



5011.0182.00



2416.0238.00



NBR: 5026.0085.00  
Desmopan: 5026.0331.00

	0 bar - 0 p.s.i				20 bar - 290 p.s.i				30 bar - 435 p.s.i				40 bar - 580 p.s.i				50 bar - 725 p.s.i						
	RPM	l/min	U.S.g.p.m.	HP	KW	l/min	U.S.g.p.m.	HP	KW	l/min	U.S.g.p.m.	HP	KW	l/min	U.S.g.p.m.	HP	KW	l/min	U.S.g.p.m.	HP	KW	kg	lb
	400	53.0	14.0	0.5	0.4	51.7	13.7	2.9	2.1	50.8	13.4	4.0	2.9	50.4	13.3	5.2	3.8	50.0	13.2	6.5	4.8	18.4	40.6
	450	59.2	15.6	0.6	0.5	57.8	15.3	3.3	2.4	56.8	15.0	4.6	3.4	56.3	14.9	5.9	4.4	55.8	14.7	7.3	5.4		
	500	65.0	17.2	0.8	0.6	63.5	16.8	3.7	2.7	62.4	16.5	5.2	3.8	61.8	16.3	6.7	4.9	61.3	16.2	8.3	6.1		
	550	71.3	18.8	0.9	0.7	69.6	18.4	4.1	3.0	68.4	18.1	5.7	4.2	67.8	17.9	7.3	5.4	67.2	17.8	9.1	6.7		