

## Universal Vacuum Booster (3 stage)

Vacuum booster draws 10 amps of power at 115 volts. Be sure to use a grounded outlet that has enough power to safely operate this device. It would be best to plug power cord into a separate circuit breaker.

Do not transport or load carpet cleaning machine with vacuum booster on top of extractor.

Always remove vacuum booster from portable cleaning unit when not in use.

Always clean intake screen after each job.

Do not use in the rain.

Lubricate the vacuum booster and or waste tank opening threads to ensure that you can always remove and install the booster with ease.

On US Products extractor, you will have to remove the safety leash/ chain from the original lid to use the booster.

On many machines you will not have to use the outer booster ring because there is already one installed on the machine. Some brands, (Mytee, Sandia, Hydroforce) you will have to remove the twist lid ring with the screw in ring that comes with the booster. Remove the wood screw from the original twist lock ring and lift the ring off the extractor. Use silicone or aquarium glue to place a bead around the perimeter of the open hole and in the old screw holes. Use the original wood screws to mount the Universal Vacuum Booster ring into the plastic. Do not over tighten the screws into the plastic. Plastic strips easier than wood does.

Warranty: One year parts, excludes shipping and labor. Power cord and switch have a 90 day parts warranty. Extended available to cover a total of 3 or 5 years.