

The Champ[®] from BLUELine



Tough, durable and dependable, BLUELine's Champ truckmount is the best choice for single wand operations. Ideal for residential and light commercial jobs.

Kohler Command 20 HP Air-Cooled Engine

Overhead valve design provides peak performance and longer engine life.

CAT 3CP 1120 Water Pump

With 4.3 gpm, pump provides high water volume for tile and hard surface cleaning. Low and high pressure shut down prevents damage to your equipment.

Gardner Denver 4M-L Vacuum Pump

Ideal for single wand commercial cleaning or restoration work. Pump is mounted horizontally for better performance and holds more oil for better lubrication.

Stainless High-Pressure Heat Exchanger

Prevents corrosion and leaking. High efficiency, high grade stainless assures maximum transfer of heat.

Heat Guard™ Bypass System

Allows unit to be operated without hooking up water for restoration work. Maintains temperature and eliminates waste by ensuring fresh hot water is not sent to the waste tank.

Stainless Steel Chemical Pump, Metering System and Check Valve

Reliable performance with no corrosion. Eliminates the frequent replacement of brass components.

Lighted Control Panel

Controls are easy to read, even when working at night.

Stainless Steel Base

Provides superior strength with no corrosion.

Easy Access

Front access to service bypass and chemical system. Easily accessible side hoses for pump and engine oil draining.

COMPACT. POWERFUL. EASY TO USE AND MAINTAIN.

INNOVATION & PERFORMANCE

Durable, dependable and designed to make your job easier, the BLUELine Champ is a compact yet powerful machine that will stand up to "real world" carpet cleaning applications.

Powered by an air-cooled 20 HP Kohler Command engine for dependable operation and longevity. With electronic ignition, full-pressure lubrication and hydraulic valve lifters, the Kohler Command engine can operate in extreme conditions.

The 3CP 1120 CAT Pump's superior design provides a water flow rate of 4.3 gpm, generating enough power and water volume for tile and hard surface cleaning. Exclusive CAT Pump high pressure seals offer unmatched performance and seal life. An oversized crankshaft has greater capacity for longer bearing life.

EASY TO USE

Its Heat Guard™ bypass system allows the Champ to operate without hook up water for restoration work.

The Champ's stainless steel chemical check valve and chemical pump ensure longer machine life and less maintenance.

A lighted control panel allows you to easily work at night. The switches and controls on the front of the machine are clearly labeled and easy to understand.

The main access panel is on the front of the machine, so you don't have to be a contortionist to service your equipment.

Electrical components are positioned above the plumbing to prevent possible shorts in the system due to a leaking hose.

The Champ comes with 100 feet of solution hose with Quick Connect, 100 feet of vacuum hose with connector, 50 feet of water inlet hose with Quick Connect, and a carpet wand.



CUSTOMER SERVICE

Our expertise in manufacturing is only surpassed by our world-class customer service. We understand that keeping equipment up and running can do more than contribute to customer satisfaction. It can provide a definite competitive advantage. BLUELine gives you that advantage.

Our parts and service experts can help you solve difficult challenges to keep your equipment in optimal condition.

We are committed to surpassing your expectations by responding to your needs as if our own success depends on it... because ultimately, it does.

SPECIFICATIONS

Engine Speed	2600 rpm (High) 1400 rpm (Idle)
Water Pump RPM	1485 rpm
Vacuum Pump RPM	3000 rpm
Water Flow Rate	4.3 GPM (maximum)
Water Pump Pressure 5M	1200 PSI (maximum)
Vacuum Relief Valve	14 inches HG
Waste Tank Capacity	70 Gallons at shutoff
Console Weight	640 lbs.
Console Weight (w/tank & hoses)	890 lbs.
Blower:	Gardner Denver 4M-L - 297 CFM
Chemical Injection System:	Stainless steel last step injection system
Disposal System:	Optional automatic waste pump-out
Engine Manufacturer/Size/Type:	Kohler Command 20 HP, air cooled.
Filtering System:	Stainless steel mesh and basket
Gauges:	Water pressure, temperature, vacuum, flow meter, hour meter
Heat Method:	Multi-stage heat exchange system - 210° - 230° F.
Recovery Tanks:	70-gallon
Shutoff System:	Recovery tank full, low oil, high temperature, low pressure, high pressure
Solution Pump:	Cat 3CP 1120 pump with stainless chemical pump and metering valve
Other:	Stainless steel base
Additional Features:	Performs restoration with no water hooked up. Ideal for tile and grout cleaning.

DIMENSIONS

Width	26"
Length	45"
Height	39"

ACCESSORIES

Electric and manual hose reels, optional holders

OPTIONAL EQUIPMENT

85-gallon sub-mount fresh water tank



*Discover why professional cleaners are switching to BLUELine.
Test drive the Champ at your authorized BLUELine dealer today.*



888-274-9500

www.steam-brite.com