



Model Number: 967207961

Husqvarna 967207961, FS 7000D TS Floor Saw, 74 hp 42in, Deutz 3 Speed E-tracking & Blade Clutch, GTIN 805544572194

Manufacturer: Husqvarna Construction Products

Husqvarna 967207961, FS 7000D TS Floor Saw, 74 hp 42in, Deutz 3 Speed E-tracking & Blade Clutch, GTIN 805544572194

Description

The modern FS 7000 D is our most powerful diesel walk-behind flat saw with low emissions, developed to be compliant with Tier 4 regulations. Ideal for concrete and asphalt cutting up to 17 1/4" deep. Suitable for mid-sized road work, service work and smaller jobs that require high production rates. It is highly versatile thanks to its high output, compact size and good maneuverability. It is equipped with an intuitive and ergonomic digital control panel with all important functions, and is easy to monitor.

Features

- Common-rail diesel engine with low emissions.
- Equipped with diesel particle filter (DPF). Complies with Stage IIIB / Tier 4 regulations.
- All important functions are easy to reach and monitor, such as blade rpm, forward speed, electronic tracking, depth gauge, belt and pulley ratios, runtime and service minder.
- The power transmission system with right-angle gearbox transmits high power to the blade shaft with optimum torque and minimised vibrations.
- Adjustable handlebars, intuitive control layout, easy manoeuvrability and low vibrations facilitate operation and reduce user-fatigue.
- Provides good visibility when cutting and can be folded for transport.
- Adjustable handles
- When thermal expansion of the concrete causes the blade to pinch in the kerf of the cut you can dis-engage the blade with the blade clutch.
- Blade guard with lockable hinge. Easy to assemble and dis-assemble using your blade wrench.
- Well-balanced design with a low profile gives you high visibility and makes it easy to handle and transport.
- Automatic adjustment of the display back light makes the display readable in all light conditions.

- The depth indicator's stop function stops the saw at your desired cutting depth. Adjustable for all blade diameters.
- The IntelliSeal blade shaft system allows for a minimum of 250 maintenance-free hours without daily greasing of bearings.
- Optimal power and speed for a wide range of blade diameters; ideal when jobs require use of multiple blade sizes.
- For easy operation and comfort.
- Helps maintain traction and gives comfortable operation.
- Electric tracking system includes position indicator on the display, it can automatically return to neutral position and has the ability to memorise last used setting.
- The blade clutch makes it possible to stop the blade when the engine is still running, for safe transportation.

Specification

ENGINE

Engine Power (As rated by the engine manufacturer) 74.3 hp
Output power at tool shaft 74 hp
Engine cooling Liquid /Air
Fuel tank volume 1352 fl oz
Cylinders 4
Number of strokes 4-stroke engine
Exhaust emissions (CO₂, EU V) 843 g/kWh

CUTTING EQUIPMENT

Arbor diameter 1"
Blade depth control Electric hydraulic
Blade diameter, max 42 in
Cutting depth, max 17.5 in

TRANSMISSION

Number of gearbox speeds 3
Transmission speed reverse 0 fpm
Transmission speed forward 250 fpm
Output shaft RPM, speed 1 1,180 rpm | 42 in (1,067 mm)
Output shaft RPM, speed 2 1,380 rpm | 36 in (914 mm)
Output shaft RPM, speed 3 1,960 rpm | 30 in (762 mm)

DIMENSIONS

Product size length 77.25 in
Product size width 38.38 in
Product size height 59 in
Weight 2,307 lbs (1,046 kg)

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >



Availability: This product was added to our catalog on Friday 11 October, 2024

Steambrite Supply