



Model Number: 84.514

Mosmatic 84.514, Car Wash Tire Cleaning System, DYF-18.5 in X 14 in

Manufacturer: Mosmatic Pressure Washing Equip

TIRE CLEANER

The water pressure makes the rotor arm begin to turn on its own. The design is constructed so simply that any maintenance work can be carried out independently and very quickly. These products are found mainly in automatic car wash facilities in the area of rim/tyre cleaning and lateral finish cleaning. It is an efficient and reliable method of achieving optimal cleaning results.

OPERATION

If water pressure is created, the rotar arm begins to turn on its own. This means that the arm is moved by the recoil force of the water stream alone and requires no additional drive. The housing with the rotar arm can be adjusted for height depending on the area in which it is being used.

POLISHED STAINLESS STEEL (INOX)

A strong and visually elegant design are a priority for all Mosmatic products. We use polished stainless steel (INOX) for all our products protecting them from rust and extreme weather conditions.

READY TO INSTALL

All Mosmatic tire cleaner are delivered pre-assembled. You can install the tire cleaner yourself by following the enclosed instructions. The cleaner is ready for immediate use after being connected to the media supply.

BROCHURE

..Learn more about spinner and swivel options

OTHER

High RPM Swivels

Swivel, triple bearing system

NW 1/4" - 3/8"

O-ring

4000

1000
90
DGL

Swivel, triple bearing system, with bulkhead fitting
NW 1/4" - 3/8"
4000
1000
90
DGG

Swivel, triple bearing system, with flange
NW 1/4" - 3/8"
4000
1000
90
DGF

Swivel, triple bearing system
NW 1/4"
Ceramic
2500
2000
40-250
DXL

Swivel, triple bearing system, with bulkhead fitting
NW 1/4"
2500
2000
40-250
DXG

Swivel, triple bearing system, with flange
NW 1/4"
2500
2000
40-250
DXF

Swivel, triple bearing system
NW 1/4"
Carbide
4000

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >

2000
250
DYL

Swivel, triple bearing system, with bulkhead fitting
NW 1/4" - 3/8"
4000
2000
250
DYG

Swivel, triple bearing system, with flange
NW 1/4"
4000
2000
250
DYF

Swivel, triple bearing system, light
NW 1/4"
5000
2000
250
DYW

Swivel, triple bearing system, reinforced
NW 1/4"
5000/7300
2000
250
DYC / DYD

Swivel, quadruple bearing system
NW 1/4" - 3/8"
5000/7300
2000
250
DYT / DYU

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >



Availability: This product was added to our catalog on Wednesday 11 April, 2012

Steambrite Supply