



Model Number: SBM3500R

Clean Storm Maintenance Repair Kit 500psi Dual 3 Stage Portable Cleaning Extractor

Manufacturer: Clean Storm

Clean Storm Dual 3 stage 500 psi - 500 psi Maintenance Kit

For Clean Storm Portables including but not limited to models: 12-3500, 12-3500-H, 12-3500-AFAD, 12-3500-H-AFAD

Even though you receive a two year parts and labor warranty on your new Clean Storm Carpet and Auto Detail Extractors, you are still required to perform maintenance on your equipment. Failure to perform maintenance voids your warranty. (This would be like you never changing the oil on your car.) Even if you purchase an extended warranty, you are still required to perform maintenance on your carpet cleaning and auto detail equipment.

This includes the following:

Rinsing filters:

Daily: waste tank ball and cage filter, auto pump out lint control (if provided).

Weekly: located in the bottom of the fresh tank, in the motor box in front of the pressure pump, filters located behind spray jets on the cleaning tool,

Monthly or every 100 hours of use: Lubrication of water pump pressure regulator, and wand valve, and Descale heating and pump system.

Yearly or every 500 hours of use: Inspect vacuum motor carbon brush length. Note if you let the spring located behind the carbon brush impact the armature it will ruin the vacuum motor. The life expectancy of a carbon brush is between 500 and 1000 hours. This is a large window so after 500 hours you will need to check the length and see how yours are wearing.

At 500 hours, Pumpteck recommends that the pump head be rebuilt and lubricated.

This package includes the three kits needed to do this.

The best way to keep track of the hours, is to install the optional hour meter on your equipment. (see below)

This package includes all the items you will need to keep your machine up and running for the next two years while your machine is under warranty:

Pumpteck: Kit "A" 500 psi Plunger & Seals Repairs 205V and 207V Pump Heads

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >

Pumptec: Kit "B" 500 psi Valves & O-Rings 10022 is for 205V
& 207V series only

Pumptec: Repair Kit "C" Cam Bearing for 400-500 Psi Models 204V,
205V, 207V, 217V .125 Stroke Replaces 0100-6005-0135

Ametek Lamb Carbon Brush for 116565-13, 116474-37, 116579-00,
115923-00 EACH

4 units for this package

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >

Kingston: Repair kit for 251-30 Valve

WD-40 3-in-one White Lithium Grease 10 oz

Shazaam: Descaler System Maintainer - 1 Gallon

Foster: 1/4in Male/Female Set Brass Quick Disconnect QD

QD O Ring Repair for Carpet Cleaning Equipment (Pair)

Strainer Filter for TeeJet With Internal Check Valve H46

Pumpteck: Brass Pressure Regulator Repair Kit for 200 to 500 psi
regulators

Please do not allow equipment, chemicals or tools to freeze. Any items that are allowed to freeze will cause the water to expand by 8% and damage it. Please install a small electric space heater on low to maintain above freezing in service van or trailer.

Optional items:

Clean Storm
SBM3AE11B

Clean Storm 120 Volt Hour Meter Panel Mount (Installed)

Clean Storm
SBM3AE11

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >

Clean Storm 120 Volt Hour Meter Panel Mount (self install)

Availability: This product was added to our catalog on Friday 19 October, 2012