



Model Number: F488

Drieaz Protimeter MMS2 Moisture Meter F488 Freight Included

Manufacturer: Drieaz

Drieaz Protimeter MMS2 Moisture Meter F488 Four-in-One Moisture Measurement System

Case is not included with this part number

Protimeter MMS2 Moisture Meter

Four-in-One Moisture Measurement System

The all-new MMS2 represents the latest Protimeter technology in an integrated, durable and easy to use design. An intuitive user interface with color screen and a comfortable, non-slip grip make the MMS2 the most useful meter you'll ever own. The MMS2 will help you tackle every restoration challenge.

PROFESSIONAL FEATURES

Pin moisture measurement. Built-in pins to quickly assess surface moisture content of a wide variety of materials, including wood, drywall, concrete, stucco, plaster and more.

Non-invasive moisture detection. Quickly locate hidden moisture and detect moisture migration. Flat-back profile ensures positive engagement with surfaces and less variability in readings.

Infra-red surface temperature reading with laser pointer.
Check surface temperatures and calculate proximity of dewpoint.

Super-fast thermo-hygrometer. Includes full psychrometric calculation tools.

SPECIAL FEATURES

Reference Reading. Measure and save readings from unaffected materials for comparison with affected areas.

Data Storage Functions. When multiple environmental readings need to be collected, the MMS2 makes it easy. Record readings instantly at the push of a button. Stores up to 8000 readings! Use the provided software to upload data to your PC to produce professional reports and documentation.

Concrete Floor Moisture Measurement. Quickly measure equilibrium relative humidity directly in concrete slabs. Simply drill a hole in the concrete, insert a humidity sleeve,

and measure!

Two-year no-hassle warranty.

Specifications:

Model

MMS2 (F488)

Display

Color LCD

Power

9V battery (included)

Moisture measurement range

Pin (% WME) 8% to 99, readings over 30% are relative.

Non-invasive (RF) up to 3/4 in. (19 mm) deep: 60 to 1000 (relative)

IR surface temperature probe range

15°-120°F | -10°-50°C

HygroStick data (nominal)

30% to 40% RH: ±3% RH at 68ºF (20ºC).

41% to 98% RH: ±2% at 68ºF (20ºC).

Range 32°F to 122°F (0°C to 50°C): ±0.6°F
(±0.3°C)

QuickStick data (nominal)

0% to 10% RH: ±3% RH at 68°F (20°C)

10% to 90% RH: ±2% RH at 68°F (20°C)

90% to 100% RH: ±3% RH at 68°F (20°C)

Range 32°F to 122°F (0°C to 50°C): ±0.6°F

Equipment: [Carpet Cleaning Machines](#) > [Vacuum Cleaners](#) > [HEPA Concrete Dust Slurry Hazmat Vacuums](#) >

($\pm 0.3^{\circ}\text{C}$)

Nominal response 30% to 90% RH and back to 30% RH in 45 seconds @
 68°F (20°C)

Data storage

Record up to 8000 results with date and time stamp from all instrument functions.

Warranty

24 months on mechanical or manufacturing defects. Does not include wearing part or accessories

[View SteamBrites Entire Selection Of Meters & Lights](#)

[MMS2 Datasheet](#)

[MMS2 Manual](#)

[MMS2 Quick Start Guide](#)

[MMS2 Flyer](#)

Drieaz Protimeter MMS2 Moisture Meter F488 Four-in-One Moisture Measurement System

Availability: This product was added to our catalog on Thursday 08 November, 2012