



Model Number: 8000-543-936

Shurflo 8000-543-936, Positive Displacement 3 Chamber Diaphragm Pump, 12volt 60psi

Manufacturer: Shurflo

Shurflo 8000-543-936 Positive Displacement 3 Chamber Diaphragm Pump 12volt 60psi

MODEL NUMBER: 8000-543-936

PUMP DESIGN: Positive Displacement 3 Chamber Diaphragm Pump

CHECK VALVE: (1-Way Operation) Prevents Reverse Flow

CAM: 3.0 Degree

MOTOR: Permanent Magnet, P/N 11-111-04 (with Special Connector)

VOLTAGE: 12 VDC Nominal

PRESSURE SWITCH: Adjustable Shut-Off (Range 40-60 PSI)

Factory Set @ 60 PSI, Turn On 45 PSI 5 PSI

LIQUID TEMPERATURE: 170 Degrees Fahrenheit (77 Degrees Centigrade) Max.

PRIME: Self-Priming Up To 5 Ft. Vertical,

Max. Inlet Pressure 30 PSI (2.1 Bar)

PORTS: 3/8"-18 NPT Female

MATERIAL OF CONSTRUCTION:

PLASTICS- Polypropylene

VALVES- Viton

DIAPHRAGM- Santoprene

FASTENERS- Zinc Plated Steel

NET WEIGHT: 4.1 Lbs (1.9 Kg)

DUTY CYCLE: Continuous (See Temperature Rise Chart)

TYPICAL APPLICATIONS: Agricultural Spraying

Shurflo 8000-543-936 Positive Displacement 3 Chamber Diaphragm Pump

12082012CEL

Availability: This product was added to our catalog on Monday 10 December, 2012