



Model Number: CH730-3015

Kohler PA-CH730-3015 20hp Command Pro Propane Engine Horizontal GTIN N/A

Manufacturer: Kohler

Propane Kohler 20 hp Command Pro V-Twin Propane Engine Electric Start CH25S CH730-3015

PA-CH730-3015

725cc,

engine mounted controls and ignition,

1” keyed crankshaft,

two stage regulator,

Propane vaporizer for liquid withdrawal,

Lock off solenoid w/filter,

20amp charging,

24 786 12-S starter side canister muffler.

PA-CH730-3015

CH730LP BASIC-WITH PANEL-KEYSWITCH

Open Loop Propane Fuel System

Kohler Command 25 HP Twin OHV Horizontal

Cylinder Type: Cast Iron Sleeves

Crankshaft: (24014381-S) 1"(25.4) x 3"(76)

Drilled & Tapped 3/8-24 UNF

.25"(6 mm) Key way

12 Volt Electric Starter: (2509811-S) Shift Style Solenoid

Key Switch: (2509930-S) Kit

Alternator: (237878-S) 15/20 Amp

Regulator: (2540320-S)

Oil Filter: (Oil Pump)

Air Cleaner: (2408302-S) Standard Duty

Liquid Fuel Withdrawal (4846501-S Vaporizer included)

Engine Weight: 106 lbs

Engine Applications: PA-64570

Sales Notes: LPG, Propane

optional: Canister muffler: (2406806-S) Starter side outlet

Panel mounted Ignition Switch

Regulator: (2440304-S)

LPG, Propane

BASIC W/PANEL KEYS LP

PA-64570

Open Loop engines have the same components as closed loop, except the ECU and oxygen sensor are not included.

Closed Loop - This system relies upon two critical parts: an analog Electronic Control Unit (ECU) and an oxygen sensor. The system's fuel metering valve, installed in the fuel line, is activated by the ECU to provide either less or more fuel. The ECU engages when the oxygen sensor, installed in the exhaust, signals a change in oxygen levels. In this way, the ECU maintains a consistent air to fuel ratio at all loads and speeds

Replaces CH640-3003

Overhead Valve Design

- Hydraulic Valve Lifters
- Cast-Iron Cylinder Liners
- PTO Sleeve Bearing (Side Load) (25 & 27 HP)
- Electronic Ignition
- Large Capacity Dual Element Air Cleaner
- High Efficiency Grass Screen and Fan
- Closed Breather System
- Stellite® Exhaust Valves
- Full Pressure Lubrication
- Large Capacity In-Line Fuel Filter

- Easy Access Valve Cover Oil Fill-Yellow
- Oil Level Dipstick-Yellow
- Large Capacity Oil Filter, Dual Oil Drain
- Oil Sentry® (Switch Installed and Wired but Unconnected)
- Variable Speed Governor
- High Performance Accelerator Pump Carburetor (25 & 27 HP)
- Fuel Shutdown Solenoid, Smart-Choke® Carburetor
- Mechanical Fuel Pump
- High Performance Spark Plugs
- 12 Volt Solenoid Shift Starter
- 20 Amp Alternator, Regulated
- Crankshaft-1.437" (36 mm) Diameter x 4.453" (113 mm) PTO Length, 0.375" (9.5 mm) Keyway, Drilled and Tapped 1.5" (38 mm) Deep, 5/8-18 UNF
- PTO Face-5.625" (143 mm) Diameter, (4 Holes) 3/8-16 x 0.67" (17 mm) Deep, 7.75" (197 mm) Diameter, (4 Holes) 7/16-14 x 0.83" (21 mm) Deep
- 7" (178 mm) Diameter Pilot
- Color-Black with Cast Aluminum

Standard Features Plus:

- Engine Controls-Key Switch, Throttle and Choke Controls
 - Fixed Grass Screen Guard (25 & 27 HP)
 - 3/16" Evaporative emissions connection
- A common replacement engine for truck mounted carpet cleaning machines and pressure washers.

Owners Manual

<https://tewarehouse.com/s.nl>
-->

Availability: This product was added to our catalog on Friday 04 October, 2013