



Model Number: CH730-3254

Kohler 25hp Command Pro Engine Horizontal CH25S PA-CH730-3254 Scag Turf Tiger Zero Turn R Mower GTIN N/A

Manufacturer: Kohler

30 DAY BACK ORDER

Kohler 25hp Command Pro V-Twin Engine Electric Start CH25S CH730-3254 Scag Turf ZTR

Replaces CH25S-68579

PA-CH730-3254

SCAG TURF ZTR

1 1/8" x 3 11/32 Crankshaft: (24014351-S)

Drilled & Tapped 7/16-20

1/4" Full Key way

12 Volt Electric Start: (2509811-S) Solenoid Shift

HD Canister Air Cleaner System

Alternator: (237878-S) 15/20 Amp

Regulator: (4140310-S)

Mechanical Fuel Pump: (2455911-S)

Oil Sensor: No

Remote Air Cleaner Adapter: (2402982-S)

(air filter Scag Supplied)

Oil Filter: (2406818S)

Oil Cooler: (5475521-S)

Oil Filter: (5205002-S)

Muffler: Canister Muffler: (2478611-S)

Fuel Tank: No

Throttle Controls: Remote: (2412656-S)

Two-year limited warranty

Engine Applications: Scag

Sales Notes:

Includes 2478611-S Muffler Kit

Also Use: PA-CH730-0066

Replaces: 68579, 68613, 68699

Popular on Scag Turf Tiger

PA-CH730-3254, CH730-3254, CH730S-0066, PA-CH730S-0066, PACH730S-0066,

CH730-0066, 68579, pa-68579, pa-68613, 68613, scag, pa-68579, ch7300066,

ch7303254, pach7303254, pach7300066

Overhead Valve Design OHV

• Hydraulic Valve Lifters

• Cast-Iron Cylinder Liners

• PTO Sleeve Bearing (Side Load) (25 & 27 HP)

• Electronic Ignition

• Large Capacity Dual Element Air Cleaner

• High Efficiency Grass Screen and Fan

• Closed Breather System

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >

- Stellite® Exhaust Valves
- Full Pressure Lubrication
- Large Capacity In-Line Fuel Filter
- Easy Access Valve Cover Oil Fill-Yellow
- Oil Level Dipstick-Yellow
- Large Capacity Oil Filter, Dual Oil Drain
- Oil Sentry® (Switch Installed and Wired but Unconnected)
- Variable Speed Governor
- High Performance Accelerator Pump Carburetor (25 & 27 HP)
- Fuel Shutdown Solenoid, Smart-Choke® Carburetor
- Mechanical Fuel Pump
- High Performance Spark Plugs
- 12 Volt Solenoid Shift Starter
- 20 Amp Alternator, Regulated
- Crankshaft-1.437" (36 mm) Diameter x 4.453" (113 mm) PTO Length, 0.375" (9.5 mm) Keyway, Drilled and Tapped 1.5" (38 mm) Deep, 5/8-18 UNF
- PTO Face-5.625" (143 mm) Diameter, (4 Holes) 3/8-16 x 0.67" (17 mm) Deep, 7.75" (197 mm) Diameter, (4 Holes) 7/16-14 x 0.83" (21 mm) Deep
- 7" (178 mm) Diameter Pilot
- Color-Black with Cast Aluminum

Standard Features Plus:

- Blower Housing to Accept Fixed Guard Blower Housing to Accept Fixed Guard
 - 3/16" Evaporative emissions connection
- Commonly used on industrial cleaning machines, pressure washers and truck mounted carpet cleaning machines

No engine controls, must be cable driven.
Owners Manual

Availability: This product was added to our catalog on Tuesday 11 February, 2014