



Model Number: U0141164G

Chemspec U0141164G, Unsmoke Air Neutralizer, 4/1 Gallon Case

Manufacturer: Chemspec

Chemspec U0141164G Unsmoke Air Neutralizer 4/1 Gallon Case  
Specially Formulated To Eliminate Stubborn Smoke and Fire Odors

Can Be Applied Directly to Burnt Surfaces. Where direct application is preferred over fogging, Air Neutralizer may be applied directly to burnt surfaces. It should be sprayed or brushed on the surfaces full strength.

Can Be Used As a Fogging Agent. Apply a solution of Air Neutralizer, diluted according to label instructions, with a fine mist fogger.

Can Be Applied Directly to Surfaces, Added to Cleaners and Paints, Or Fogged  
Chemspec's Air Neutralizer formulation lets you apply it by the most effective yet economical method. This means that Air Neutralizer can be applied as dictated by the intensity of the odor and/or accessibility to the surface. This ability to be applied by multiple methods gives you the flexibility to choose the most cost-efficient method in order to achieve the optimum results.

Can Be Used As An Additive. As an additive to wall-cleaning solution, use 3 ounces of Air Neutralizer per diluted gallon of cleaner. To water-based paint, use 4 ounces of Air Neutralizer per gallon of paint. To carpet and upholstery shampoo, or detergents, use 1 ounce of Air Neutralizer per diluted gallon of shampoo/detergent.

Special Formula Neutralizer For Smoke and Fire Odors?The special formulation of Air Neutralizer absorbs the strongest smoke and fire odors. This product doesn't just mask the odors, it actually removes odors associated with burnt materials and smoke. Contains highly absorbent glycols.

Unsmoke® Air Neutralizer

Product Description

Unsmoke® Air Neutralizer is specifically formulated to eliminate smoke and fire odors from hard surfaces and textiles.

Available Sizes

• 1 gal. / 3.8 L bottle (U0141164G - Case of Four)

• 5 gal. / 18.9 L (AN5G - Single)

Product Specifications

• Form: Liquid

• RTU pH: 7.0

Note: Cover furniture, paintings, clothes or any objects subject to attack by solvents.

Avoid overwetting.

FOR INTERIOR AIR DEODORIZING:

Mix 22 ozs. to 1 gallon of water. Use fine mist setting on cold fogger. Repeat treatment if necessary.

FOR BURNT SURFACES:

Use full strength. Apply with a natural fiber brush.

AS AN ADDITIVE:

To wall cleaning solution: use 3 ozs. per diluted gallon. To water-based paint, use 4

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >

ozs. per gallon.

For carpet and upholstery shampoo:

Use 1 oz. per diluted gallon to cut soot and deodorize textiles.

FOR REMOVING CIGARETTE ODORS:

Add 3 ozs. to regular cleaning solution. Will remove tar and nicotine from all surfaces.

Unsmoke&trade; Air Neutralizer (AGHS SDS - US/CA English - 7-09-2015)

Unsmoke&trade; Air Neutralizer (1 Gal) (GHS Label)

Unsmoke&trade; Air Neutralizer (5 Gal) (GHS Label)

Unsmoke&trade; Air Neutralizer (Product Image - Web)

Unsmoke&trade; Air Neutralizer (Product Image - Print)

Availability: This product was added to our catalog on Sunday 06 February, 2005