



Model Number: 32346

Kleenrite 32346 Sphere Portable Extractor 200psi 1/3 Vacs Poly Tank Immersion and Preheater 15ft Hose Set 1.25in

Manufacturer: KleenRite

Kleenrite 32346 Sphere Portable Extractor 200psi 1/3 Vacs Poly Tank Immersion and Preheater 15ft Hose Set 1.25in

Capacity: 4 gallon solution tank / 3.5 gallon waste tank

Dimensions: 25 1/2" L x 13 1/2" W x 27 1/2" H

Compatibility: Water based solutions only

Lids: Roto-molded, hinged, flap lid on solution tank/Clear view poly dome lid on vacuum tank. The Sphere has a threaded clear vacuum tank lid with inner receiving ring gasket for positive seal. Vacuum connection is mounted on the "lift-off" vacuum tank/waste bucket. When the clear poly lid is removed, an opening is provided for cleaning of the waste tank and ball float shut-off screen.

Construction: Rotationally molded, faux granite finish, polyethylene solution tank and vacuum tank assembly. Rotationally molded black base with "rain gutter" lip between tanks, base and internal components provides spill proof operation when filling solution tank. All Switches are located on the vacuum tank/solution output side for spill proof operation and easy operator access. Solution and vacuum hose connections are located on the front/switch panel side of the units. Vacuum tank lifts off and doubles as a waste bucket. "Pig Tail" power cord(s) are located on the back of the unit. Unit is easily moved by using the vacuum tank handle. The units roll easily on 4 - 3" swivel casters. 14/3 safety yellow "easy-detach" power cord(s) included. Units also include a 15' high PSI rated solution hose, 15' - 1 1/4" vacuum hose. Units can be upgraded to provide 25' solution and vacuum hose sets. Carpet and upholstery tools are sold separately.

Pump: Models are available with the choice of a 60 PSI or 100 PSI diaphragm demand/bypass pump, or 200 PSI, preset pressure, piston pump.

Vacuum(s): Models are available with the choice of a single 2-stage vacuum or single 3-stage vacuum. All the vacuums are epoxy coated, high efficiency, 5.7" and UL recognized.

Vacuum(s) Configuration Ratings:

Single 2-stage - 92" of lift and 100 CFM

Single 3-stage - 137" of lift and 101CFM

Heater(s):

Immersion Heater - Some models are available with the choice of a 1750 watt immersion heater fixed in a Stainless Steel solution tank which is enclosed in the

roto-molded solution tank housing. These, select unit choices, allow the solution in the solution tank to preheat up to 190 degrees prior to activating the pump and vacuum thus, allowing the machine to operate on a single 15 amp power supply. To obtain maximum efficiency it is recommended that the solution tank be filled with the hottest tap water prior to turning on the heater. The immersion heater is thermostatically controlled to 190 degrees with an additional high limit safety shut-off thermostat which, if activated, must be manually reset .

Heat Exchanger – Some models are available with 1750 watts of heat. Heater cartridges are inserted into the center of a 6 pound aluminum heat exchanger for maximum efficiency. Solution is pumped through the heat exchanger from the solution tank and heated prior to exiting the machine on an “on demand basis”. To obtain maximum efficiency it is recommended that the solution tank be filled with the hottest tap water prior to activating the pump, vacuum, and heater. Heater cartridges can be replaced without having to replace the entire heat exchanger. Heater is thermostatically controlled to 190 degrees with auxiliary thermostat for high limit safety shut-off. Components are covered by an insulated housing for added protection. Models with heat exchangers are dual cord units – 15 amps each circuit.

Serviceability: The Sphere models have an “easy access” base that is easily removed by loosening 2 bolts, on the bottom of the unit, when it is turned upside down. Components can easily be replaced with a few simple tools in a very short time. Components utilize a plug in system for wiring so each component can be easily unplugged and replaced.

Confused about carpet cleaning machine and what to purchase? Read article on How to narrow down you portable carpet cleaning extractor search.

Options:

Shazaam
Business Package



Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >

Shazaam: Business Starter Package

Samco
SM09802-HC



Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >

Samco: Straight Partition, Stair, and Under-The-Bed Wand for Carpet
Cleaning

Producton Metal Forming
U1560PSB-M



Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >

PMF: Detailer Internal Spray Economy w/ Brass Valve Upholstery Cleaning, Auto Detail, And Mattress Wand U1560PSB With Male QD and Filter

Shazaam
150-53



Shazaam: Extra Hose Set - 25ft x 1.5in - Vacuum & 1/4in Solution with QD installed

Solo
456HD-C



Solo: 2 Gal Chemical Resistant Plastic Sprayer 456HD Pump Up with Viton
Seals Carpet Cleaner Package

HydroForce
AB24

Hydro-Force: Grandi Groomer Carpet Rake

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >

SBMW



Extended Warranties for Equipment Valued up to 7499.99 Available

Availability: This product was added to our catalog on Sunday 06 February, 2005