

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >



Model Number: F337
Drieaz Protimeter MMS Plus Moisture Meter
Manufacturer: Drieaz

Item #F337

GE PROTIMETER MMS PIUS SPECS

Model
F337

Gross Weight
10.58 oz (300 g)

Dimensions (HxWxD)
7 x 2.5 x 1.9"
(180 x 70 x 49 mm)

Max. needle depth

0.4" (10 mm)

Display

LCD

Batteries (included)
2 AA batteries

Measurement range
Pin (% WME)

6 to 99.9%

Non-invasive (RF)
0 to 1000 (relative)
up to 1" (25.4 mm) deep

Humistick® (RH)
0 to 100% RH,
32°F to 122°F (0°C to 50°C)

Temp. probe range

15°F to 120°F (-10°C to 50°C)

Humistick® data
0 to 10% RH

10 to 90% RH

90 to 100% RH

32°F to 122°F
(0°C to 50°C)

±3%RH at 68-86°F
(20-30°C)
±2%RH at 68-86°F
(20-30°C)
±3%RH at 68-86°F
(20-30°C)

$\pm 0.6^{\circ}\text{F}$
($\pm 0.3^{\circ}\text{C}$)

The complete MMS includes:

available)

- Humistick[®] probe (Hygrostick probe
- Humistick[®] extension lead
- Heavy-duty pin extension lead
- Surface temperature sensor
- 5" deep wall probes
- Calibration check device
- Spare pins
- Data download software
- Data cable
- Nylon carry pouch
- Instructions

Dri-Eaz presents the
GE Protimeter MMS Plus
Moisture Measurement System + Logging
NEW — Full Range RH!
Measures 0-100% RH and 32-122[°]F with new
Humistick[®] probe (also compatible with Hygrostick[®] probe)
Three meters in one
The complete meter package! The MMS Plus system combines
three different meter functions into one convenient unit, plus it serves as a data
logger. It's a revolutionary tool, one that's ideal for the restorer that wants to update to
an all-in-one system.

Hygrometer Mode
Measures the relative humidity, temperature, dewpoint, proximity to dewpoint, and grains per pound (GPP) with the modular, replaceable Protimeter Hygrostick®.

Pin Measure Mode
Use the penetrating pins to determine the moisture content of wood and the Wood Moisture Equivalent (WME) value of other building materials. Add an optional Hammer Electrode to increase versatility.

Pinless Measure Mode
Uses non-invasive radio frequencies to detect the presence of moisture without damaging materials.

Data Logger
Stores up to 1,000 results (with date and time stamp) for downloading to your computer. Allows you to keep clear records of drying conditions that help to safeguard your business and protect your customers.

We want to continuously provide the best products and services to you, our customer. As part of our ongoing commitment to offering the best tools and support possible, we have launched some enhancements to our Return Material Authorization (RMA) online tool for Protimeter products.

Adding to the fast response, improved visibility to returns and ease of doing business with GE, the following enhancements are available beginning on April 9th, 2012:

Repair option added in drop-down box (in addition to Replace option) for the following instruments:

Aquant
Psyclone
Surveymaster

Hygrohawk
Hygromaster
MMS

Mini
Timbermaster

Hammer Electrode added with repair option.

The online RMA process has reduced our turnaround time from receipt of product to ship replacements in less than 48 hours. The following link will take you to our online RMA tool for the Protimeter products.

A onetime registration will be required to login and start the RMA process.
<https://www.ge-mcs.com/RMAProtimeter/pages/login.jsf>

Please remember that we have changed the Protimeter manufacturer's warranty from 12 to 24 months.

3 MONTH WARRANTY EXTENSION AVAILABLE by registering new products at: www.registeryourmeter.com for a total Warranty of 27 Months!

Availability: This product was added to our catalog on Sunday 06 February, 2005