



Model Number: 4902-4212

Shurflo 4902-4212, 12volts 45psi 4gpm, Accumulator Combo with filter, (shurflo refuses to fill order)

Manufacturer: Shurflo

Model

4902-4212 Also marketed under part number 68-000

Description

12 VDC

4.0 GPM [15.1 LPM]

/ Accumulator Combo w/ 2 gallon [7.57 Liter] stainless steel accumulator tank.

Pump Specs: EPDM valves, Santoprene® diaphragm, 45 PSI

Maximum
Flow
GPM/LPM

4 pgm

Maximum
AMPS

9.5

Shut-OFF
Pressure

45 PSI [3.1 Bar]

.Brochure and more information

Installation instructions ..

The most advance system available, this fully-automatic, quit unit pumps tasteless, odorless water smoothly and consistently. Corrosion resistance and NSF certified tank.

Multi-fixture marine fresh water installations. Other uses may included 12V DC pressurized water systems in cabins This pump may be used for general water transfer for carpet cleaning machines and for boats. For other applications, contact SHURflo

PUMP

Type: 4 Chamber Diaphragm
Ports: 1/2" -14 NPSM-Male.
Liquid: 130 °F [54 °C] Max
Prime: 6 feet [1.82 M]
Inlet PSI: 30 PSI [2.1 Bar] Max
Run Dry: Yes

ELECTRICAL

Motor: 12VDC Permanent Magnet, Intermittent Duty
Protection: Thermal Overload, Automatic Restart
Leads: 14 AWG, 16" [40 cm] Red +, 13" [33 cm] Black -
Fuse: 15 Amp Recommended
Control: Adjustable Switch. Shut-Off 45 PSI [3.1 Bar] ± 5 PSI [0.4 Bar]
Restart 25 PSI [1.8 Bar] ± 5 PSI [0.4 Ba

20110525dj

Availability: This product was added to our catalog on Thursday 10 January, 2008