



Model Number: F405

Drieaz F405 Sto and Go Ducting with storage bag Freight Included

Manufacturer: Drieaz

Drieaz Sto & Go Ducting F405 Stow

Item #F405

Sto & Go

Easily ventilate hard-to-reach spaces. Includes 25 feet of collapsible 12-inch ducting. Connect one or more sections of ducting to the Vortex Axial Fan for powerful ventilation.

Recommended for use with:

Nikro US4000 Duct Cleaner and Air Scrubber

Ebac PF400 Axial

Drieaz 2800i

Drieaz 3500i

Drieaz Air Wolf

Vortex Axial Fan

DriStorm Blast

STO & GO SPECS:

Model

F405 G1795726

5UNZ9

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >

Temperature Range
-20°F to 180°F / -29°C to 82°C

Material
PVC Flame Retardant Vinyl

Product Features

- Built-in bag with sturdy handle contains and protects ducting during transport and storage
- Semi-rigid ducting constructed with spring steel wire helix resists collapse under negative pressure
- Black reinforcement strips protect internal wire to ensure long service life
- Made of PVC-coated polyester fabric
- Temperature range: -20 to 180 degree F
- ASIN: B00AB255L6
- Shipping Weight: 22 pounds

10130115djc

Drieaz Sto & Go Ducting F405 Stow

Drieaz AirWolf Hardwood Floor Drying Unit F228 230volt

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >

AirWolf
Item #F228-230V

AIRWOLF SPECS

Model
F228

Height
17" / 43 cm


Width
21" / 53 cm

Depth
16" / 41 cm

Weight
35 lb / 16 kg

Motor

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >



1.0 hp

Motor Speeds
1-speed

Max. CFM
(Free Air)
800

Max. CFM (Full Load)
450

Static Pressure
(Free Air)
7.75" / 19.7 cm

Static Pressure
(Full Load)
5" / 13 cm

Power (Free Air)
11.6 amps

Power (Full Load)
8.5 amps

Stackable
Yes

UL Listed
Yes

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >

AirWolf/WolfPack Hardwood Floor Drying System

Dry Hardwoods Fast!

The AirWolf uses an unbeatable combination of CFM and static pressure to literally force water out of damaged hardwood floors. The WolfPack system directs the high-velocity airflow of the AirWolf into the flutes between the flooring and the subfloor. This way the floor actually dries from the bottom out.

Avoid Refinishing Costs

The AirWolf/WolfPack can dry out a hardwood floor in as little as 3 days! By drying fast from beneath, the AirWolf/WolfPack system can help reduce or eliminate cupping and associated refinishing costs. This means no sanding! Now that's a valuable service to offer your customers.

The world's best hardwood floor drying system
Up to 800 CFM and 7.75" of static pressure
Powerful 1.0 hp motor
Stack the AirWolf for storage
Carrying case included for WolfPack attachments

-->

Availability: This product was added to our catalog on Friday 08 February, 2008