



Model Number: EZ4035G

General Pump EZ4035G, Assy For SGP-4035 8.905-293.0 3.5gpm 4000psi 3400 rpm, Freight Included

Manufacturer: General Pump

General Pump Assy, Sgp-4035, General Ez4035g - 8.905-293.0

- Standard SAE J609 gasoline mounting flange for up to 13 hp engines
- Forged brass manifold with an exclusive lifetime warranty and 3:1 hydrostatic rating
- Die-cast, anodized aluminum, oil-bath crankcase
- Innovative one-piece plunger design to eliminate water entering crankcase
- Premium roller bearing
- 5% reduction in crankcase load compared to standard 3,000 psi, 15 mm pumps
- Unitized stainless steel inlet and discharge valves

Maximum Volume
3.5 gpm

Max. Discharge Pressure
4000 psi

Maximum Pump Speed
3400 rpm

Maximum Inlet Pressure
125 psi

Maximum Inlet Vacuum
3 ft. water (2.6 in. Hg)

Bore
.512 in / 13 mm

Stroke

Equipment: [Carpet Cleaning Machines](#) > [Vacuum Cleaners](#) > [HEPA Concrete Dust Slurry Hazmat Vacuums](#) >

.433 in / 11 mm

Crankcase Oil Capacity
14.0 oz

Maximum Fluid Temperature
165°F

Inlet Port Thread
1/2-14 BSPP-F

Discharge Port Thread
3/8-19 BSPP-F

Hollow Shaft I.D.
1.0 in / 25.4 mm

Weight
20 lbs

Dimensions
8.8 x 9.7 x 6.5 in

Sales Brochure and Schematics

General pump Maintenance Guide
Sales tax collected in CA and TX

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >



Availability: This product was added to our catalog on Tuesday 03 June, 2014

Steambrite Supply