



Model Number: Ti410

Gardner Denver TriFlow Ti410 Sutorbilt 708 CFM Truck Mount Vac Blower 791249 Pump 86175370  
TI650 GYCPJCA0203 107629

Manufacturer: Gardner Denver Product

TriFlow 410 Sutorbilt Tri-Flw 650 cfm 13 hp Truck mount vacuum blower 107629

Is used on: Prochem Everest 650 (Hyundai Engine) truckmount and  
Sapphire Scientific 870 and Big Gulp 4500 Flood pumper truckmount

Sapphire Scientific Big Gulp 4500 Flood Pumper Truckmount Auto Pump Out

Original part number 791249

New part number 86175370, 8.617-537.0

GYCPJCA-0169, GYCPJCA-0176, GYCPJCA-0204

Also marketed under # PP86175370, TL 410 RHBD-HORZ, Ti410, Ti650

Compare to:

Sapphire Scientific 46-059 Right Hand Crank, Clock Wise Rotation, Bottom  
discharge.

Q. What is the difference between

GYCPJCA-0169, GYCPJCA-0203 and GYCPJCA0204?

GYCPJCA-0176

GYCPJCA0203

Legend Brands Cleaning 107629

Answer: "0203" - sight glass on right hand side of gear case when facing the drive  
shaft.

The "0169" does not have this feature. the "0204" was just assigned to Prochem for  
the Everest Truckmounts.

Gardner Denver is shaping the standards of performance and reliability in the  
design of positive  
displacement blowers and vacuum pumps. The tradition continues with the TriFlow  
Series vacuum  
pumps. Each TriFlow is engineered for a wide range of commercial and industrial  
applications. Specifically,  
TriFlow is the choice of leading Original Equipment Manufacturers (OEMs) of truck  
mounted vacuum

cleaning systems. TriFlow offers operators significant benefits and advantages:

- Great performance and efficiency in a compact design
- Quiet operation
- Highest quality materials and construction
- Flexible installation capability
- Reduced maintenance
- Available in 3 sizes – 406, 408 & 410
- TriFlow delivers
  - Vacuum to 16" Hg and Flows to 700 cfm (open flow)
- Leading OEM choice for vacuum cleaning systems
- Patented Tri-Lobe Design for quiet operation and low pulsation
- Heavy-duty design for reduced downtime
- Advanced oil/air seals for reliable oil-free air delivery
- Independent oil sumps prevent cross contamination and allow the vacuum pump to operate safely on an incline when used in carpet cleaning applications
- The inlet and outlet ports include both flange and FNPT connections for ease of plumbing
- More than 5,000 units in active operation to date

TriFlow: Setting the Industry Standard Quiet Operation

- Three lobe impeller geometry allows higher throughput while creating lower pulsation levels than two lobe units, resulting in reduced noise
- An internal feedback porting arrangement contributes to the further reduction of noise

Quality Promise

- Backed by one of the largest distributor networks in the industry
  - Every TriFlow vacuum pump is built under rigid ISO 9001:2000 quality standards
  - Each TriFlow is individually tested to meet rigorous performance specifications
  - Factory Warranty Period
    - Factory 18 months from the date of shipment to SteamBrite from Factory or 12 month from date of installation - whatever occurs first.
- All sales final. Optional extended warranty available.

Quality Construction

Each model incorporates the following for longer service life, reduced downtime and maintenance

- Highly reliable Dual Splash Lubrication
- Heavy duty bearings
- High strength timing gears
- Integral heat dissipation fins on the case to help maintain proper clearances

## Oil-Free air Delivery

- Piston ring seals are incorporated on each impeller shaft with a lip seal on the drive shaft, providing superior sealing to prevent oil leakage into the air chamber
  - Independent oil sumps prevent cross contamination and allow the vacuum pump to operate safely on an incline when used in carpet cleaning applications
- Build in oil level sight windows.

## Flexible Installation

- Unique, integral mounting surfaces are precision machined for ease of installation and drive system alignment
- Critical mounting dimensions are similar to those of existing two lobe positive displacement vacuum pumps allowing for system upgrades
- The inlet and outlet ports include both flange and FNPT connections for ease of plumbing

TI410 Out of Box Weight 211 lbs.

## A RHBD or Right Hand Bottom Discharge

TriFlow may also be used as a THRD or Top Hand Right Discharge. These are the only 2 ways to configure a RHBD machine. The "hand" refers to where the drive shaft is.

Factory recommends synthetic lubricant called PD Aeon

## Optional

Gardner Denver 28G46 Brand Blower Oil Aeon PD-XD Full Synthetic Formula  
Extra Heavy Duty for High Heat Applications 28G47-QT  
All blowers shipped without oil. Please add oil to your shopping cart.

*Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >*

Brochure

Model Matrix

Prochem Truckmount Blowers used is the past

---

*Availability: This product was added to our catalog on Monday 19 January, 2009*