



Model Number: FK2BH2B

Foster FK2BH2B, QD 1/4in Male/Female Set, Brass Quick Disconnect, Compatible With Carpet and Tile Cleaning Machines

Manufacturer: Foster

Foster FK2BH2B: 1/4in Male and Female Brass Quick Disconnect QD

Buy More, \$ave More

Description

FHK,TWO WAY SHUT-OFF

Both socket and plug are sealed at disconnect.

Standard industrial interchange design, most widely used in industry. Within each series, only sockets and plugs of the same size will couple together. Conforms with ISO 7241-1, Series B.

Manual - Socket sleeve must be manually retracted to connect and disconnect.

Standard seals are Buna-N.

Rated pressures as defined by ANSI/B93.2-1986, based on 4:1 safety factor and non-shock service.

Specification

QTY: 1 Set, 2 PC

Material: Brass

Interchange: ISO 7241-1, Series B

Type: FHK, Two Way Shut off

Country/Region of Manufacture: United States

MPN: H2B - K2B (1 Set)

Body Type: 1/4" Valve

Thread Type: 1/4" Female NPT, FPT

Includes

Foster FK2B Bretco 1/4in Male Brass Quick Disconnect QD Nipple Plug  
Coupler  
ONE

Foster QD 1/4in Female Brass Quick Disconnect Mytee B102 25-001 FH2B  
8.697-350.0 Socket Coupler  
ONE

Set-Up

- ONEWAY SHUT-OFF: Suffix VA to either socket or plug catalog number for valve

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >

actuator.

- STRAIGHT-THRU: Suffix LV to both socket and plug catalog number for less valve.
- BL: Locks against accidental disconnect. To connect, align ball with slot. After connection, rotate sleeve to lock. To disconnect, realign ball with slot and retract sleeve.

Optional

1/4in Stainless Steel In Line Ball Bearing Live Hose and Wand Swivel MXF  
3500 Psi [8.712-457.0] 421034 (makes your work easier)  
Mounts on wand or mounts on the end of your solution hose.

Important information:

Coronavirus Prevention and treatment Procedures Cleaners and Supplies  
Step By Step 11136038

Availability: This product was added to our catalog on Thursday 27 August, 2009