



Model Number: 4230SGF-20G3

Pressure Pro Stationary HOT Washer 4230SGF-20G3 Natural Gas LP 3.8gpm 2000psi 6hp 230v 3ph 16 amp General Pump

Manufacturer: Pressure Pro

Pressure Pro Stationary HOT Washer 4230SGF-20G3 Natural Gas LP 3.8gpm 2000psi 6hp 230v 3ph 16 amp General Pump

Specify either LP (liquid propane) or NG (natural gas) when ordering.

## STANDARD FEATURES

Rugged powder coated steel frame, enclosed pump/motor compartment w/ hinged lid

Super efficient schedule 80 coil

Factory Installed

Pressure Pro PCA750-10 Replacement Burner Coil for 2-3 Gpm Pressure Washers

Stainless steel coil wrapper,

Factory Installed

Pressure Pro Stainless Coil Wrap PCA750-6 Fits Hot Shot Vertical 2-3 GPM Models

Control panel,  
Float tank

Factory Installed

Pressure Pro Float Tank Assembly YFLOATTANK 1.05 gallons

Robert Shaw LP/NG electronic ignition 24 volt controls

Factory Installed  
Robertshaw Natural Gas and Propane Valve

Commercial/Industrial grade motor

Factory Installed  
Baldor Motor CEM3615T 5 Hp 3 Phase 3450 RPM 184T Frame 230 /460  
Volts 6.7 Amps

Low speed V-belt driven General pump

Factory Installed  
General Pump HTXS1812S Emperor Run 3.2/3.8gpm 2000psi  
1450/1750rpm High Temperature

or similar

High limit over temp protection

Factory Installed  
225 Degree Switch Sensor 1/2" Mip with 3 Wire Leads

Controls water temperature.

## Vacuum switch

Factory Installed  
Mecline Vacuum Switch MVVS2.5

Used to control solenoids, Relays, and Low and No water safety switches.

## Safety pressure relief valve

Factory Installed  
Pressure Pro 22533A-4600 5000psi 3/8Mip 6 gpm 140 degree Pressure  
Relief Valve

Protects coil from over pressurization.

## 10' power cord (no plug)

NOTE: All units are completely factory assembled, tested in the USA, and delivered ready to operate.

## STANDARD ACCESSORIES

Gun/wand assembly with insulated grip and quick connects

Factory Provided  
Pressure Pro AGUD3621290C Washer Lance and Gun Combo 4060 psi  
Insulated Grip 36 in w Couplers

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >

50' prime; high pressure hose w/quick connects

Factory Provided  
Pressure Pro AHS330 Double Wire 50 ft Washer Hose 3/8 In 6000psi With  
Couplers Installed Black

Maxi-Flo 20% chemical injector assembly w/quick connects

Factory Provided  
Pressure Pro ACI005 General Pump 100775 Maxi-Flow Fixed 20%  
Chemical Injector 3-5 gpm

4 color-coded QC spray nozzles

Factory Provided  
Pressure Washing Nozzles, and Repair Parts

1 color-coded QC chemical soap injection nozzle

General pump Maintenance Guide

Owners Manual

Factory Warranty

Factory Brochure

Cleaning Units/Speed: 15,200  
AVAILABLE OPTIONS

98-010 Panel Mount Thermostat \$100

General Pump 100538 Dial Thermostat 86 - 250 Degrees F. 781999

Parts plus labor to be added

98-011 Hour Meter

Factory Installed

Digital Hour Meter 120 Volts, EI 24-277 Ac/Dc 50/60 Hz - 8.749-316.0

Perfect for oil change and descaling intervals

98-101 10" Draft Diverter \$185.83

98-102 Soap Solenoid w/ Panel Mount Switch \$106.56

98-104 Time-delay Shutdown w/ Adjustable Timer \$308.00

98-105 Single Remote Station w/ Start/Stop/Burner \$201.86

98-106 Multi Remote Stations w/ Start/Stop/Burner/Soap \$344.82

98-107 Add'l Remote Stations \$265.12

98-108 Oil Fired Option \$238.69

Optional Factory installed

Beckett 240 Volt AFG Oil Burner 8.709-326.0 Pressure Pro301 VMG202

98-130 By-Pass Thermal Shutdown \$89.66

98-510 18/5 Cable, Single Remote Station \$1.16 per ft

98-512 18/7 Cable, Multi Remote Stations \$1.39 per ft

General Pump Oil

General Pump Oil Case 24 units

Equipment: [Carpet Cleaning Machines](#) > [Vacuum Cleaners](#) > [HEPA Concrete Dust Slurry Hazmat Vacuums](#) >

Required at 50 hours and then every 200 hours

Descaler

Shazaam: Descaler System Maintainer - 1 Gallon

Required every 100 hours of use.

All Stainless Steel Frame Models Available &ndash; consult sales rep

Availability: This product was added to our catalog on Saturday 24 January, 2015