



Model Number: RKA55G30HN

AR Pump RKA55G30HN, 3000 psi 5.5 gpm 1750 rpm 24mm Shaft, 8.751-885.0 Rka5.5g30hn

Manufacturer: Annovi Reverberi Pumps

AR Pump RKA5.5G30HN 3000 psi 5.5 gpm 1750 rpm 24mm Shaft

RKA5.5G30HN Plunger pumps are designed for a wide variety of high pressure washing applications. They are constructed of die-cast bodies and feature a brass head. Internal components include special thick solid ceramic plungers for long life and durability. Precision cast cooling fins are anodized for maximum heat dissipation

RK-Series Pumps

Precision cast cooling fins are anodized for maximum heat dissipation.

Oversized tapered roller bearings and the precision supports assure proper shaft alignment and maximum life. Valve cages of special designed Ultra-Form provide positive seating and extended life. One-piece connecting rods are either a special alloy aluminum or bronze oversized for strength and load disbursement. These pumps are designed for gearbox , belt drive, or coupling drive systems, electric motor 182-184 frame driven systems, or gasoline engine driven systems.

Flows: 5.5 GPM

Pressure to: 3000 PSI

Speeds: 1750 rpm

Shaft Styles: Solid Shaft 24mm,

Break Horse Power: 11

Stroke MM 13.8

Max Water Temp: 140 degrees F.

Inlet Thread: 1/2" Fip

Max Liters Per Min: 20.8

Max Bar: 205

Bore Dia. MM: 20

Weight Lbs: 20

Oil Capacity: 15 oz

Discharge Thread: 3/8" Fip

AR pumps are a combination of exceptional degree of technology and innovation, quality and reliability worthy of a leading brand on the market. The wide range includes many models which vary in terms of pressure, deliver, power and technical characteristics, to satisfy widely different market demands.

Factory Brochure

Freight charges will be applied to ALL orders. (Including local pickup in San Antonio

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >

TX)
20150727jp

Availability: This product was added to our catalog on Wednesday 17 June, 2015