



Model Number: RCV2G25D-F7

AR Pump RCV2G25D-F7, 2500psi 2 gpm Gas Bolt On 3/4 Shaft 3400rpm

Manufacturer: Annovi Reverberi Pumps

AR Pump RCV2G2500D-F7

2500 psi

2 gpm

Gas Bolt On 3/4 Hollow Shaft

11 lbs

3400 rpm

Bore Dia: 15mm

Stroke: 4.4 mm

Pressure Washer Pumps & Parts - RCV2G25D-F7

FEATURES - RCV2G25D-F7

- Manifold: High strength forged brass for long term use.
- Bolts: Eight 6mm.
- Plungers: NEW Ceramic Plungers, thicker wall to help prevent thermal shock.
- Valves: Stainless Steel, valve seat o-ring is side mounted.
- Seals: High quality high pressure seals. NEW low-pressure seal with a built in scraper.
- Piston Guides: Two piece guides.
- Drive End: NEW connecting rod with 12% more load surface. Large side cover sight glass, over sized bearing. Rear cover oil drain.
- Crankshaft: Forged, precision ground.

AR Pump RCV2G25D-F7 Manufacturer Specs (.PDF format)

SPECIFICATIONS - RCV2G25D-F7

Maximum Volume

Max. Discharge Pressure

Max. Horsepower

Stroke

Maximum Fluid Temperature

Inlet Port Thread

Maximum Inlet Vacuum

Maximum Inlet Pressure

Bore

Weight

Crankcase Oil Capacity

Discharge Port Thread

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >

- 2.0 gpm
- 2500 psi
- 3.4 EBHP
- 4.4 mm
- 140°F
- 1/2 F
- 8.0 LMP
- 170 psi
- 15 mm
- 11 lbs.
- 9.81 oz
- 3/8 F

20150727jp

Freight charges will be applied to ALL orders. (Including local pickup in San Antonio, TX)

Availability: This product was added to our catalog on Saturday 04 July, 2015