



Model Number: CL3619TM

Baldor Motor CL3619TM 3.0Hp Single-Phase 1725 RPM 184TC Frame 230 Volts 13.2 Amps

Manufacturer: Baldor Motors

Baldor Motor CL3619TM 3.0Hp Single-Phase 1725 RPM 184TC Frame - 230 Volts  
13.2 Amps

81lbs

Output	3.0 hp
Phase	1
Synchronous Speed	1,800 rpm
Frequency	60 Hz
Voltage	230 V
Enclosure	TEFC
Frame Material	Steel
Frame	184TC
XP Division	Not Applicable
Brand	Baldor-Reliance
Agency Approvals	CSA / UR
Ambient Temperature	40 &deg;C
Auxillary Box	No Auxillary Box
Auxillary Box Lead Termination	None
Base Indicator	RG
Bearing Grease Type	POLYREX EM (-20F +300F)
Blower	None
Current	13.2 A
Design Code	L
Drip Cover	No Drip Cover
Duty Rating	CONT
Efficiency @ 100% Load	81.5%
Electrically Isolated Bearing	No electrically isolated
Feedback Device	No feedback
Front Face Code	Standard
Front Shaft Indicator	None
Heater Indicator	No heater
High Voltage Full Load Amps	13.2 A
Insulation Class	F
Inverter Code	Not inverter
KVA Code	H

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >

Lifting Lugs	No Lifting Lugs
Locked Bearing Indicator	Locked Bearing
Motor Lead Exit	KO Box
Motor Lead Quantity/Wire Size	2 @ 14 AWG, A PH
Motor Lead Termination	Flying Leads
Motor Standards	NEMA
Motor Type	3634LC
Number of Poles	4
Overall Length	16.54 in
Power Factor	90
Product Family	General Purpose
Pulley End Bearing Type	Ball Bearing
Pulley Face Code	C-Face
Pulley Shaft Indicator	Standard
Rodent Screen	No Rodent Screen
Service Factor	1.00
Shaft Diameter	1.125 in
Shaft Extension Location	Pulley End
Shaft Ground Indicator	No Shaft Grounding
Shaft Rotation	Reversible
Shaft Slinger Indicator	No Slinger
Speed	1,725 rpm
Speed Code	Single Speed
Starting Method	DOL
Thermal Device - Bearing	None
Thermal Device - Winding	Do Not Use
Vibration Sensor Indicator	No Vibration Sensor
Winding Thermal 1	Manual Thermal Overload
Winding Thermal 1 Location	KO
Winding Thermal 2	None

Availability: This product was added to our catalog on Tuesday 05 January, 2016