



Model Number: 80409

PumpTec 80409 HTU-231-1/2HP Hydrostatic Test Unit 1/2 HP 120 Volt 500psi GTIN: N/A

Manufacturer: Pumptec

Hydrostatic Test pump, Series 356 pump, continuous-Duty Open Drip Proof 1/2 HP motor, 35' cord with GFCI, Adjustable pressure unloader valve, liquid filled pressure gauge, quick connect garden hose inlet, quick connect 3/8 outlet, heavy duty non-conductive mounting rails and grommets. Use to top off glycol systems.

Features:

- Heavy Duty Handle -- Epoxy-coded with grip
- On-Off Switch -- protected from moisture and physical damage
- Continuous-Duty -- Totally enclosed fan cooled 3/4 HP motor
- Quick Connect -- garden hose connects in a "snap"
- 35' Cord -- SJTW weather resistant UL.
- Pressure Gauge -- 0-600 PSI liquid filled Industrial grade
- Adjustable Pressure -- 0-500 PSI with by-pass unloader valve
- Quick connect -- 3/8 NPT(F) outlet easily to test components
- Non-conductive mounting rails -- rust proof with heavy duty pads. Keeps unit high and dry when used outdoors
- Safe GFCI protection -- Electricity to unit is automatically shut-off if any short occur

PumpTec: AS1200 Water Otter 1200 psi Pressure washer pump and tile and carpet cleaning pump

OPTIONAL

Faucet Adapter 13/16s to Garden Hose Connection

OPTIONAL

Clean Storm Auto Fill Hose 6 ft By 1/2 Inch ID with 90 degree Fitting for Hot water Garden Hose

Optional

Shower Head Hot Water Hook Up Kit SBM1834

Optional

Clean Storm Automatic Fill Kit for Carpet and Tile Cleaning Machines

- * Commercial Duty
 - * American-Made Pump and Motor
 - * 1,200 psi, 2.2 GPM at Nozzle Tip (turn down pressure if you like to as low as 200 psi)
 - * 14.3 Amp High Efficiency Motor
 - * Maintenance-Free 1,200 psi Pump
 - * 1,000 Hour Continuous, Full Load Rated
 - * Simple Repair, Low Cost Parts
 - * Each Component The Best Available
 - * GFCI with 35' Cord (120 volt versions only)
 - * Female Garden Hose Inlet
 - * 1/4 Female Quick Connect Outlet
 - * Max Water Temperature 140 degrees
 - * 120 Volt, 8 to 15 amps (depending on pressure), 240 volt version is this amp draw cut in half.
- fitted with an m44 motor, this is the motor used for a hard surface pumping system that is outside the extractor case.
Does come with a pressure gauge.
Out of box measurements 14" X 11" 11" H
Shipping wt: 50#s
Shipping dimensions: 20" X 16" X 15"
Amp draw is 7.5 amps to turn on + 1 amp for each 200 psi you ask it to push.
Example 500 psi uses 10 amps @ 120 volts

Current or past OEM Associations:

CWS-HDS1200

80346

20-0640

AS1200

Cross American Shock-Wave

Pressure washer motor information below:

Parts list

Brochure

Start Up Procedures

PumpTec Warranty Info .Options:

Add an extended Warranty to your cleaning equipment;

<http://www.steam-brite.com/extended-warranties-equipment-valued-749999-available-p-10663.html>

717510409055



Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >

Four (4) Way Faucet Key J40-005

Note Pumptec Dealers do not receive the faucet adapter, connection hose, or free sipping. Just the pump at dealer prices + shipping

Compare to other tile and carpet cleaning pump systems:

<http://www.steam-bright.net/showthread.php?2048-Tile-cleaning-pump-options-to-add-to-my-flood-pumper-or-carpet-cleaning-machine&highlight=tile+cleaning+pump>

Rotovac \$795
used to be \$685.78 our of CO
-->

Availability: This product was added to our catalog on Tuesday 31 January, 2017