



Model Number: CH752-3102

Kohler 27hp Command Pro Horizontal Engine PA-CH752-3102 747cc With Key Switch and Throttle control GTIN N/A

Manufacturer: Kohler

Kohler 27hp Command Pro Horizontal Engine PA-CH752-3102 747cc With Key Switch and Throttle control

Overview

Kohler engines have gone beyond just horsepower and torque to become the standard in the utility engine industry. U.S.A.

Idle speed 1650 rpm

High speed 3750 rpm

With key switch with throttle control

Crankshaft 24014150, 1.437" (1 7/16", 36 mm) Diameter x 4.453" (113 mm) PTO Length,

0.375" (9.5 mm) Keyway, Drilled and Tapped 1.5" (38 mm) Deep, 5/8-18 UNF

• PTO Face-5.625" (143 mm) Diameter, (4 Holes) 3/8-16 x 0.67" (17 mm) Deep, 7.75" (197 mm) Diameter, (4 Holes) 7/16-14 x 0.83" (21 mm) Deep

• 7" (178 mm) Diameter Pilot

27 hp Command Pro V-twin

(New 2014 HP label)

747cc V-Twin Engine

1-7/16" x 4.41" keyed shaft,

tapped 5/8" w/3/8" keyway.

Should be set up for remote operation.

Heavy Duty Snorkle air cleaner system.

OHV, cast iron cylinder liners, full pressure lube w/ oil filter,

engine mounted oil cooler, fuel pump,

12 volt electric start w/ 20amp alternator,

less gas tank, less muffler.

2 year warranty.

Model CH752-3100.

115 lbs

Engine Type:

4-cycle, gasoline, OHV, cast iron cylinder liners, aluminum block

Model

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >

Command PRO CH752

J1940 Power hp(kW) 1
27 (20.1)

Displacement cu in (cc)
45.6 (747)

Bore in (mm)
3.3 (83)

Stroke in (mm)
2.7 (69)

Peak Torque lbs. ft (Nm)
42.2 (57.2)

Compression Ratio
9.1:1

Dry Weight lbs (kg)
105 (48)

Oil Capacity U.S. quarts (L)
2 (1.9)

Lubrication
Full pressure w/full-flow filter

Dimensions L x W x H in
14.6 x 17.7 x 24.5

Backpressure Limit 2
50

Equipment: [Carpet Cleaning Machines](#) > [Vacuum Cleaners](#) > [HEPA Concrete Dust Slurry Hazmat Vacuums](#) >

J1995 Power hp (kW) 3
26 (19.4)

J1995 Rated Speed (RPM)
3600

Kohler 30 HP
CH750S-0005 PRO
1.125" x 4" Crankshaft
Drilled & Tapped 7/16-20 UNF
.25" Keyway
12 Volt Electric Start (Solenoid Shift Style)
25 Amp Alternator (Regulated)
Oil Sentry (no connected)
Keyswitch-Engine Mounted Controls
Standard Dual Element Air Cleaner
PTO Sleeve Bearing
Mechanical Fuel Pump
Stellite Exhaust Valves
Cast Iron Cylinder Sleeves
Two Barrel Carburetor
Closed Breather System
Digital Spark Advance System
Hydraulic Valve Lifters
Controls: Manual
Shipping Weight = 120 lbs

Manufacturer Warranty: 24 months parts / 24 months labor
Owners Manual

Availability: This product was added to our catalog on Tuesday 17 October, 2017