Model Number: 50211

Sonin 50211 Moisture Test Meter (8.697-031.0)

Manufacturer: -

Sonin Moisture Test Meter (8.697-031.0)
Dual-reading scale gives relative (1-10) and moisture percentages 10-28% readings.

    Contact probes are on a 3'-coiled cable for detecting moisture in hard to reach spots
    The 10-point scale corresponds to moisture levels from 10-28%
    Scale and reference chart correlate relative and moisture percentage readings
    Great for inspectors, contactors and homeowners
    Test hard or soft wood, concrete, plaster, carpet and more to determine the extent of moisture problems
    Find out if potentially damaging excess moisture is present
    Locate and trace roof leaks and water seepage; assess the extent of wet rot and hidden condensation
    Use it to check surfaces before painting, wallpapering or laying floors or tile
    Helps you to select drier lumber
    Requires one 9V battery (not included)
    Instruction sheet included
    One-year warranty
    The Sonin Rapitest Moisture Test Meter is the number one selling product of its kind in terms of unit sales. It is a great tool for the professional contractor, inspector, or homeowner that needs an extremely affordable and accurate moisture-testing product. This unit will detect moisture in a range from 10% to 28% and has an easy to understand analog gauge.
    Features:

 • Dual scale gives relative (1-10) & moisture percentages (10-28%) readings
 • Contact probes are on a 3' coiled cable for testing in hard to reach spots
 • On / Off Switch
 • Built in battery tester
 • Great for Inspectors, Contractors & Homeowners
 • Find out if potentially damaging excess moisture is present
 • Test hard or soft wood, concrete, plaster, carpet & more to determine the extent of moisture problems.
 • Locate and trace roof leaks & water seepage; assess the extent of wet rot & hidden condensation.
 • Use it to check surfaces before painting, wallpapering, laying floors or tile.
 • Helps you to select drier lumber.
 •

Cross Reference Skus

86970310

50211
8.697-031.0

Specifications:

• Range: 10 to 28%
• Dimensions: 4.75" x 2.75" x 1.5"
• Cord length: 36" coiled wire
• Probes: (2) 5/8" deep pin needles (spaced 3/8" apart)
• Power: (1) 9 volt alkaline battery (not included)