



Model Number: 8.620-112.0

Flojet 8.620-112.0, ET508 ltt Flow Control Oscillator Pump, 220/240V 50Hz, (86201120) 1/8 fip ports

Manufacturer: Flojet

This small Flojet pump is used to repair most small spotter and small upholstery cleaning machines.

Flojet model 55psi 0.40gpm open flow, 115VAC, Viton elastomers, 1/8" NPT Female ports - (no hose barbs included) chemical resistant pump for spotting machines.

Including and not limited to original Mytee Lite 2 extractors, Mytee Tempo, Durrmaids extractors, Sandia SpotX extractors, Windsor Presto, MutiSprayer, Olympus, Prochem... that used 55 psi pumps
Flojet ET508 Oscillating Pump

Designed for general consumer, commercial and industrial applications. All models are self-priming, double insulated and built to draw low amps for cool operation.

Model No.: ET508 Series

ET508

Flojet ET508 FNPT Oscillating Pump

Voltage

220/240V, 50Hz (8.620-112.0)

Check Valve

Viton

Port Type

1/8" (3.2 mm) FNPT

Dimensions (H x W x D)

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >

2.11 x 2.25 x 4.53 (inches)
53.5 x 53.6 x 115.0 (mm)

Factory Brochure

Internal Bypass PERFORMANCE SPECIFICATIONS

PUMP Coil Motor 230 VAC Max Amps

0.48 @ 0 PSI (0.0 bar)

Liquid Temperature Max 160°F (72°C)

Dry Vac 7 ft (6.0 inches Hg)

Wet Vac..... 12.5 ft (11.0 inches Hg)

Flow Rates*HP0.37 GPM @ 0 PSI (0.0 bar)

Nominal BypassHP55 PSI (3.8 bar)

Nominal *Open flow rate may vary +/- 15% depending on installation

Compare to current or past OEM Associations:

Windsor Presto Mini PRS and PRSJ

8.620-112.0

86201120

4039784363748

40142016

WN86201120

Optional 1/8" Npt by 1/4" barbed brass fitting AKA 32004

Availability: This product was added to our catalog on Wednesday 23 May, 2018