



Model Number: 9202C

Hypro 9202C, Pedestal Pump, for Belt drive Truckmount Auto Dump

Manufacturer: Hypro Pumps

Hypro 9202C Pedestal Pump for Truckmount Auto Dump

Series 9202C features a pedestal mount, direct drive, Viton® seals, *CCW pump shaft rotation (9203C-R is CW) and a glass-filled nylon impeller with stainless steel wear ring. Maximum fluid temperature is 140 Deg. F.

Max rpm: 6000

Produces up to 180 psi

5/8" shaft

1-1/4" fip water in connection X 1" Fip water out connection.

Viton seals and glass filled nylon impeller with stainless steel wear ring.

Works with hot water up to 140 degrees F.

Can be run at a one to one speed with an engine.

Usually set on the floor and sucks water from out of a "tee" fitting on truckmount drain valve.

Can run dry without damage.

If used with a vacuum tank, install a check valve on discharge side.

Factory installed on many different models of Amtex truckmounts.

Will not self prime unless the water level is higher than the suction side port.

Compare to current or past OEM associations:

UPC

698035174485

Requires that you

Optional

Brass Check Valve 1in Fip X 1in Fip 8.709-386.0

Required and not included: Must use some type of water filter system on inbound side of pump. Example Mytee F200

Mytee F200 Hose Mount Lint Hog Debris Carpet Cleaning Machine Hose Filter for 2 inch vacuum hose

Equipment: [Carpet Cleaning Machines](#) > [Vacuum Cleaners](#) > [HEPA Concrete Dust Slurry Hazmat Vacuums](#) >



Availability: This product was added to our catalog on Tuesday 20 November, 2018

Steambrite Supply