



Model Number: 305GAC6010

Gardner Denver 305GAC6010, Sutorbilt Legend 4MP PD Gardner Denver KIT-OVERHAUL, 4in (R and S) VERSION LS GRS-SPL

Manufacturer: Gardner Denver Product

Gardner Denver 305GAC6010 Sutorbilt Legend 4MP PD Gardner Denver KIT-OVERHAUL 4" "R&S" VERSION LS GRS-SPL

This webpage is for the rebuild kit only.

Gardner Denver understands the complex needs and challenges of carpet cleaning industry and offers a unique range of carpet cleaning blowers/vacuum pumps known for their excellent performance and low maintenance.

4" Gear with 5" Wide blades

Sutorbilt Legend DSL

&ndash; Pressure to 15 psig

&ndash; Vacuum to 16" Hg

&ndash; Airflow to 400 cfm

&ndash; 24/30 Warranty from date of manufacture.

Max discharge Temp 285 degrees F.

2-1/2" Female Pipe Connections.

Turn at up to 3600 rpm.

Lubrication: Grease on one side and Splash Lube on the other end.

• Legendary 75 years of proven results and most recognized name in the industry

• Operating temperatures are up to 15&deg;F cooler compared to leading competitive brands for longer bearing life

• Greater durability with an increased capacity for overhung load by as much as 30%

• Unmatched weight, rigidity and strength protect against bearing wear, rotor contact and overall package vibration

• Universal mounting feet allows for easy field conversion

Commonly used with 25 horse power truckmounts.

4" Crankcase Gear with 5" Wide Blades

Mounts vertically or horizontally (feet included) and can be spun in either direction.

Even with with wand on the floor pulling 10" Hg the 4MR moves an incredible 358 CFM!

Prochem Truck Mount Blower Comparison

Shipping box is 21" X 15" X 15"

Prochem Truck Mount Vacuum Blower Pump

Prochem - Bear, Bruin, Bruin II, Legend SE, Legend XL, Legend AD, &amp;

Performer.  
Bridgepoint - Lancer & Lancer II (2)  
Legend GT 4M-L  
Blue Baron 45XL  
Sears Techmaster (Bruin II) 4M-L  
Performer w/Cat  
Legend GT, SE, AD, XL  
Bruin & Bruin II  
Lancer & Lancer II  
Cyclone 2 AD & Cyclone XL  
800A & Bear                      Specs: 270 CFM @14" Hg

Specs:  
330 cfm @ 13" Hg  
359 CFM @ 3600 RPM  
Why different specs? Some models turn the blower faster than others and reading are taken at different restrictions.

Compare to Current or Past OEM Associations:  
RTS4MP - Medium Pressure  
Prochem 41-905021  
Prochem 86190700  
Prochem 8.619-070.0  
8619-0700  
PP41-905021  
905021  
4MR  
4M-L  
RTS4MP  
4MVL (4" Gear, Medium Pressure, Vertical Mount, Left side exhaust)  
4ML  
4MVR (4" Gear, Medium Pressure, Vertical Mount, Right side exhaust)  
GACMDRA-0084  
GACMDPA  
GACMBPA  
4MVP  
TS-GD-4MP  
48524  
GACMAPA0064  
GACMDRA, RHC (Right Hand Crank)  
GACMARA THC (Top Hand Crank)  
GACMBRA BHC (Bottom Hand Crank)  
GACMCRA LHC (Left Hand Crank)  
GACMDRA  
4MR-RHC-S LS GRS-SPL  
Prochem 69-908, Prochem 46-097  
Sapphire Scientific 69-980  
GACMDSA0084  
4MS-RHC-SLSGRS-SPL

GACMASA0084 (top hand crank)

(Note, just move the feet to the bottom and the oil breather to the top port to change from THC, BHC, LHC, RHC)

- Horizontal and vertical mounting

- Replaces Sutorbilt California B, F, L and P Series

- ISO 9001 certified

Factory Brochure

Mounts vertically or horizontally (feet included) and can be spun in either direction.

Shipping box is 21" X 15" X 15"

Shipping wt w/pallet: 160 Lbs.

The Sutorbilt blower operates by trapping air with two "figure eight" impellers rotating in opposite directions. This entrapment occurs four times per revolution and efficiently creates pressure and volume for your aeration system.

The Sutorbilt Legend Series features machined cast iron construction of the housing and impellers. Impellers are dynamically balanced to operate without vibration and are permanently fastened to steel shafts. Shaft rotation can be in either direction. To change the inlet/discharge orientation of the blower simply reverse the rotation of the drive motor.

Anti-friction bearings are used throughout. Timing gears and gear end bearings are splash oil lubricated from an oil-tight housing enclosing the timing gears. Drive end bearings are grease lubricated through fittings. High temperature Viton lip type seals prevent the oil and grease from entering the impeller chamber to prevent contamination in your system.

Machines are shipped without oil. Do not operate before reading the operation manual and adding lubricant.

Optional

Gardner Denver Brand Blower Oil Aeon PD-XD Full Synthetic Formula Extra Heavy Duty for High Heat Applications 28G47-QT

<https://www.blockerandwallace.com/4MR-Sutorbilt-Legend-Prodview.html> \$1945  
20181220 -->

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >

Availability: This product was added to our catalog on Wednesday 20 March, 2019

Steambrite Supply