



Model Number: PA-CV752-3000

Kohler PA-CV752-3000 27hp Command Pro V-Twin Vertical Engine Electric Start CV30S

PA-CV750-3005 In Stock GTIN N/A

Manufacturer: Kohler

Kohler 30hp Command Pro V-Twin Vertical Engine Electric Start CV750-3005

Also marketed under CV750-0004 and CV30S, CV752-3000

Durable, Long Life Design.

Hydraulic valve lifters are oil pressurized, ensuring that push rods stay in constant contact with the rocker arms. Requiring no adjustment, the valve train is virtually maintenance-free. In addition, full-pressure lubrication delivers continuous lube to critical engine components, even at 25-degree angle of operation and optional oil cooler regulates the oil temperature extending oil-change intervals. Large capacity, in-line fuel filter provides extra protection against dirt particles that can clog fuel lines.

High Power Performance.

Overhead valve technology provides greater volumetric efficiency and a higher compression ratio. This produces more power, improved fuel economy and cooling and reduces oil consumption. In addition, there is virtually no carbon buildup, reducing overall maintenance costs. The variable speed, mechanical governor promises smooth performance, regardless of application or fluctuating demands for power.

Reliable Starting.

Kohler Command PRO®; electronic ignition system generates a stronger spark at low cranking speed and Automatic Compression Release (ACR) allows compression to escape during cranking to reduce pull force.

User-Friendly Maintenance.

High Power Performance.

Reliability and Long Life Design.

Quiet, Smooth Operation.

Easy Dependable Starts.

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >

Engine Type:

4-cycle, gasoline, OHV, cast iron cylinder liners, aluminum block

Model

Command PRO CV750

Max Power @3600 RPM hp (kW) 1  
30 (22.4)

Displacement cu in (cc)  
45.0 (747)

Bore in (mm)  
3.3 (83)

Stroke in (mm)  
2.7 (69)

Max Torque lbs. ft (Nm)<sup>1</sup>  
44 (59.6)

Compression Ratio  
9.4:1

Dry Weight lbs (kg)  
105 (47)

Oil Capacity U.S. quarts (L)  
2 (1.9)

Lubrication  
Full pressure w/full-flow filter

Dimensions L x W x H in  
20.5 x 17.7 x 22.5

Backpressure Limit 2  
50

J1995 Power hp (kW) 3  
26 (19.4)

J1995 Torque lbs ft (Nm) 3  
37.9 (51.4)

\* Length is blower housing to air cleaner. Width is spark plug to spark plug. Height is top of air cleaner cover to mounting feet.

<sup>1</sup> Max Power (hp) and Max Torque (lbs ft) specifications for Kohler general purpose engines are rated pursuant to Society of Automotive Engineers (SAE) J1940 based on gross output testing performed according to SAE J1995 without the air cleaner and muffler. Actual engine power and torque are lower and affected by accessories (air

cleaner, exhaust, charging, cooling, fuel pump, etc.), application, engine speed, ambient operating conditions (temperature, humidity and altitude) and other factors. This J1940 / J1995 rating provides consistent measurement to customers who may want to control the intake and exhaust features of the engine. For more information, contact Kohler Co. Engine Engineering Department. Kohler Co. reserves the right to change product specifications, designs and standard equipment without notice and without incurring obligation.

2 Inches of H2O @ 3600 RPM WOT

3 J1995 power and torque certified by 3rd Party Witness

Kohler Videos

Owners Manual

Service Manual

<https://www.smallenginesuppliers.com/shop/agora.cgi>

\$849

-->

Standard Features:

- Overhead Valve Design
- Hydraulic Valve Lifters
- Electronic Ignition
- Cast-Iron Cylinder Liners
- PTO Sleeve Bearing (Side Load)
- Digital Spark Advance System
- Heavy Duty Canister Air Cleaner System
- Closed Breather System
- High Efficiency Grass Screen and Fan
- Stellite® Exhaust Valves
- Full Pressure Lubrication
- Large Capacity In-Line Fuel Filter
- Easy Access Fill Tube and Dipstick-Yellow
- Large Capacity Oil Filter
- Dual Oil Drain
- Oil Sentry® (Switch Installed and Wired- Unconnected)
- Canister Muffler with Heat Shield, Oil Filter Side Outlet

- Variable Speed Governor
  - Two-Barrel Carburetor
  - Fuel Shutdown Solenoid
  - Smart-Choke® Carburetor
  - Pulse Fuel Pump
  - High Performance Spark Plugs
  - 12 Volt Solenoid Shift Starter
  - 20 Amp Alternator, Regulated
  - Crankshaft - 1.125" (28.5 mm) Diameter x 3.16" (80 mm) PTO Length, 0.25" (6 mm) Keyway, Drilled and Tapped 1.5" (38 mm) Deep, 7/16-20 UNF
  - PTO Face - 10" (254 mm) Diameter, 4 Through Holes, 0.36" (9 mm) Diameter
- Color-Black with Cast Aluminum

#### Standard Features Plus:

- Special Chopper Grass Screen and Fixed Guard
- Kohler HDAC
- 3/16" Evaporative emissions connection

#### Overview

Kohler 23hp Command Pro V-Twin Vertical Engine Electric Start 1in x 4in Shaft  
CV23S-75565-70231

Kohler 23 HP Command Pro V-Twin OHV Vertical Engine. Replacement for Great Dane Zero Turn Radius mower. This 23 HP peak performer features a steel-forged vertical shaft and air-cooling in a V-Twin configuration. U.S.A.

#### Features + Benefits

- 12V solenoid shift starter
- Aluminum block
- Spin-on oil filter
- Oil Sentry
- Includes muffler and exhaust manifold

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >

Key Specs

Engine Displacement (cc)

674

Start Type

Electric

Application

Great Dane Zero turn radius mower

Engine Type

Command Pro V-Twin CV23 - OHV

Rated Power (HP)

23

Torque (ft./lbs.)

40.2

Displacement (cu. in.)

41.1

Shaft Output

Vertical

Shaft Diameter (in.)

1

Shaft Length (in.)

4

Shaft End Tapped (Diameter (in.)/Threads per inch)

7/16 - 20

Shaft Rotation (From PTO Shaft Side)

Counterclockwise

Cylinders (qty.)

2

Cylinder Bore

Cast iron

Bore x Stroke (in.)

3.15 x 2.64

Compression Ratio

8.5:1



Cooling System

Air cooled

Air Cleaner Type

Dual element air filter with foam pre-cleaner

Fuel Tank

Not included

Fuel Type

Gasoline

Fuel Pump

Pulse

Fuel Filter

In line

Oil Capacity (qt.)

2

Lubrication System

Full pressure

Ignition System

Electronic

Carburetor

Fuel injection

Max. RPM

3,600

Charging System Amps

20

Muffler Included

Yes

Auto Compression Release

Yes

Bolt Circle (in.)

10

Dimensions L x W x H (in.)

21 3/16 x 17 11/16 x 14 5/16

EPA/CARB Approval (California Air Resource Board)

Yes

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >

## Manufacturer Warranty

24 months parts / 24 months labor

## Ship Weight

108.0 lbs

## Item#

70231

Manufacturer Warranty: 24 months parts / 24 months labor

-->

Availability: This product was added to our catalog on Monday 17 January, 2011