



Model Number: GPE-75EH-3-3

Gillette Generator GPE75EH-3-3 13hp Industrial Portable Generator 6000watts 240 volt, electric start, triple phase

Manufacturer: Gillette Generator

Gillette Generator GPE75EH Industrial Portable Generator 7500watts 120volts electric start

Powered By Honda's GX390 Commercial Grade OHV Engine

- A compact, fuel efficient engine which provides plenty of torque
- Cast iron cylinder sleeve provides long engine life

Electric Starting System w/ Recoil Backup (Battery Not Included)

- Start your generator by flipping a switch (Min 200 CCA Battery)

Oil Alert® Warning System

- Alerts you or shuts engine down if oil reaches an unsafe level

Exclusive Kleen-Power® (Only 6% THD) & Exclusive Power-Assist™

- Provides clean, smooth operation of sensitive electronics
- Provides extra power for hard starting electric motor loads

Full Panel GFCI Protection - OSHA & UL Compliant

- Must use GFI type manual transfer switch for panel connection
- Interlock kits are not compatible with this generator

4-Gallon Metal Fuel Tank w/ Gauge, Twist-Cap & Slop Valve

- Provides extended run times of 4.2 hours @ 3/4 load

Rugged 1.25" Steel Round Roll Frame

- Provides total generator protection on the jobsite

Built-In Hour Meter w/ Maintenance Alerts

- Reminds you when it is time to change the oil & air filter

2 Year/1000 Hour Limited Warranty

GENERATOR MODEL

GPE-75EH

MAX. KW @ 3 PH.
6

PRIME KW @ 3 PH.
5.5

PRIME AMPS @ 208 V.
18

PRIME AMPS @ 240 V.
16

PRIME AMPS @ 480 V.
8

GENERATOR REGULATION
5 % VOLTAGE REGULATION ON SINGLE PHASE GEN-SETS.

FREQUENCY REGULATION
5 %, (3 HERTZ) FREQUENCY REGULATION FROM NAME PLATE RATING

“KLEEN-POWER”™
ELECTRICAL WAVEFORM DISTORTION IS LIMITED TO JUST 6 % ON ALL
GEN- PRO GEN-SETS

ENGINE MODEL (WARRANTY)
HONDA GX390 O.H.V. (3 YEARS)

ENGINE START METHOD
12VDC ELECTRIC & ROPE RECOIL

ENGINE HP @ 3600 RPM
13 HP

ENGINE DISPLACEMENT
1 CYLINDER, 23.7 CU. IN. (390 CC)

ENGINE AIR CLEANER
HEAVY DUTY, LOW PROFILE, DUAL ELEMENT FILTERS

ENGINE FUEL TANK
8 GAL. (30.2 L.) METAL FUEL TANK WITH GAUGE, TWIST-CAP, & SLOSH VALVE

ENGINE OIL SYSTEM
FORCED SPLASH

LOW OIL PROTECTION
AUTOMATIC ENGINE SHUTDOWN PROTECTION AT LOW OIL LEVEL

db(A) AT 7 METERS
78

3/4 LOAD RUN TIME (HRS)
8.4

FUEL USE, GAL/LTR/HR
0.95 / 3.56

MOTOR START POWER
2 1/2 HP, CODE G ELECTRIC MOTOR

CRANE PICK-UP HOOK
OPTIONAL EQUIPMENT : CENTRAL PICK-UP ON TOP OF GEN-SET

2-WHEEL DOLLY KIT
OPTIONAL EQUIPMENT : COMPLETE WITH (2) HANDLES AND
"NEVER GO FLAT" WHEELS

MAINLINE CB
STANDARD 3 POLE MAG CIRCUIT BREAKER - 20A @ 208V &
240V & 10A @ 480V

HOURLY METER
RUN TIME HOURS, PLUS (3) MAINTENANCE ALERTS: 25 HOUR CHANGE
OIL, 25 HOUR CHANGE OIL FILTER, 25 HOUR SERVICE AIR FILTER

POWER TAKE OFF
POWER TAKE OFF 4 POSITION TERMINAL STRIP

PROTECTIVE ROLL FRAME
RUGGED 1-1/4" ROUND ROLL FRAME, PROTECTING ENTIRE
GEN-SET

LENGTH, INCHES
31

WIDTH, INCHES
25

HEIGHT, INCHES
27.5

SHIP WEIGHT, LBS.
277

CU. FEET SHIP BOX
20

Optional

Generator Grounding Kit Bonding Parts 18012017 Self Install

Equipment: [Carpet Cleaning Machines](#) > [Vacuum Cleaners](#) > [HEPA Concrete Dust Slurry Hazmat Vacuums](#) >

BE Pressure 85.508.003 Champion Power 48036 L14-30P X Four 5-20R
Generator Power Cord Adapter

Availability: This product was added to our catalog on Monday 13 April, 2020