



Model Number: 6312.0450.10

Comet Pump 6312.0450.10, Assembly 3000 psi 2.5 Gpm, Slap Happy 3/4 Shaft, 3400 RPM

Manufacturer: Comet Pump

Comet Pump 6312.0450.10 Assembly 3000 psi 2.5 Gpm Slap Happy 3/4 Shaft 3400 RPM

## Product Description

Comet DWD-K 2530 G 3,000 PSI 2.3 GPM Commercial Duty Triplex Plunger Pump Fully Plumbed with Adjustable Unloader and Chemical Injector

### Features:

- Direct Drive with Gas Flange 4-7 HP SAE (2-9/16 center to center)
- Forged brass manifold and ceramic plungers to prevent pitting and wear
- Built-in unloader and chemical injector for quick plug and play on systems
- Lubricated double seal packings to increase pump longevity (high & low)
- Anodized crankcase to protect from the harshest elements
- Ceramic Plungers
- Stainless steel check valves to keep pump at optimal performance.
- Featuring a 3/4" hollow shaft with flange for coupling to gas engines.

### ADDITIONAL FEATURES OF PLUMBED MADE READY PUMP:

- 3 Foot soap hose with filter
- 3/8" QC plug
- Thermal relief valve
- Garden hose adapter with spring

Comet DWD G-K Data Sheet

### Specifications:

- Max. Volume: 2.3 GPM
- Max. Discharge Pressure: 3,000 PSI
- Max. Pump Speed: 3,400 RPM
- Shaft Diameter: 3/4" Hollow
- Maximum Horsepower Requirements: 6.3 GHP
- Inlet Port: 3/4" GH (garden hose)
- Outlet Port: 22M-14 Male Twist Connect with 3/8" QC Plug
- Note: Optional D10088 3/8" QD Coupler shown below
- Weight: 11.55 lb.

Availability: This product was added to our catalog on Tuesday 25 May, 2021