



Model Number: 10058

Pumptec 10058, X-Series Valve Kit, GTIN 10679065073129

Manufacturer: Pumptec

Pumptec 10058 X-Series Valve Kit

Compare to current or past OEM associations:

10058

PT-10058

10679065073129

Description

Pumptec X-Series powerful high-flow pump ideal for area sprays, pest control, fire protection, and turf, lawn & agricultural applications! Pumptec pump X-Series with solid ceramic 4 plunger type design is the most efficient way possible to pressurize water. This efficiency produces up to 20% more pressure or flow for a given power input compared to competitive pumps. The series offers a variety of pump and motor combinations customized to meet specific application requirements. Typical applications include pressure cleaning, Pest spraying and misting. All pumps are factory lubricated for long-life Performance. The only tool to completely disassemble the pump to its basic components is a 3/16" hex wrench. Durability and Performance results from exclusive use of premium materials. All metallic wetted parts are stainless steel. An aircraft-grade anodized aluminum pump with Teflon hard-coat body is nearly indestructible compared to pumps made of castings. The body offers chemical compatibility with a wide variety of chemicals. Epoxy and other coatings are available for high and low pH applications. Flow and pressure can be optimized to exactly match power input to nozzle size, and offers an assortment of eccentrics for low, medium and high pressure to match your application requirement.

Features

- Performance Features
- Long Life
- High-Pressure
- High-Efficiency
- Serviceability
- Durability
- Application Flexibility
- Chemical Compatibility
- Compact Design
- Enhanced Priming

Specifications

Body: Hardcoat Aluminum
Plunger: Ceramic
Valves: Stainless Steel
Inlet Port: (1) - 1/2" NPT (F)
Discharge Port: (1) - 1/2" NPT (F)
Max Fluid Temp.(°F): 140
Max Pressure (PSI): 75
Open Flow (GPM): 6.40
Seals: PTFE/FKM
O-rings: FKM

Downloads & Related Content

X-Series Owner Instructions & Parts Manual

Performance Chart

Dimensional Images

View Demonstration Video

View Rebuild Video

Pumpteck Limited Warranty

PUMPTEC INC., as a manufacturer warrants to the original purchaser of each new pump or other product of its own manufacture, for a period of one year from the date of shipment from the factory to be free from defects in material and workmanship under NORMAL use and service. "NORMAL use and service" means not to operate in excess of recommended maximum speeds, pressures, temperatures (140 degrees F, 140oF) or handling fluids not compatible with component materials and/or not according to PUMPTEC INC. specifications for purchased product. This warranty doesn't not apply to any pump or other product which has been repaired or altered to affect the performance or reliability of the pump or any other product, or any other product altering the overall performance not obtained from PUMPTEC INC.

Please Read Full Warranty

<https://www.qspray.com/pumpteck-hoop-plungers-kit-x-series-10058/> \$67.99

-->

Availability: This product was added to our catalog on Thursday 16 September, 2021