



Model Number: 81788

Pumptec 81788 X-3 Series M960 Plus Sub Assembly 12v 56 Frame 60 Amp 3/4 HP GTIN 10679065073211

Manufacturer: Pumptec

Pumptec 81788 X-3 Series 12V Pump Motor Set 5 GPM 60 Amp KFM Stainless Valves 100 Psi

Manufacturer Description:

Includes 50 ft hose, gun, regulator, and Inlet filter system.

Factory Provided

Pumptec M960 MDI Motor CIM 3/4 HP 12V 56 FRAME 1725 rpm Replaces M60-8

Pumptec pump X-Series with plunger type design is the most efficient way possible to pressurize water. This efficiency produces up to 20% more pressure or flow for a given power input compared to competitive pumps. The series offers a variety of pump and motor combinations customized to meet specific application requirements. Typical applications include pressure cleaning, Pest spraying and misting. All pumps are factory lubricated for long-life performance. The only tool to completely disassemble the pump to its basic components is a 3/16" hex wrench. Durability and performance results from exclusive use of premium materials. All metallic wetted parts are stainless steel. An aircraft-grade anodized aluminum pump with Teflon hard-coat body is nearly indestructible compared to pumps made of castings. The body offers chemical compatibility with a wide variety of chemicals. Epoxy and other coatings are available for high and low pH applications. Flow and pressure can be optimized to exactly match power input to nozzle size, and offers an assortment of eccentrics for low, medium and high pressure to match your application requirement.

#### Performance Features

- Long Life
- High-Pressure
- High-Efficiency
- Serviceability
- Durability
- Application Flexibility
- Chemical Compatibility
- Compact Design
- Enhanced Priming

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >

## Features:

Voltage: 12 VDC  
Max flow: 5 gpm  
Max pressure: 100 psi  
Port sizes: (1) 1/2" FNPT inlet, (2) 1/2" FNPT outlet  
Housing: Anodized aluminum  
Seals: T-Seal  
Valves: Stainless steel  
O-rings: KFM  
Max draw: 60  
Max fluid temperature: 140&deg;F  
Weight: 36 lbs

Factory Brochure

Availability: This product was added to our catalog on Monday 27 September, 2021