



Model Number: 24012-017

Winco Generators WL12000HE-03/C 50A Package Industrial Portable Generators 12000 Watt  
GX630cc HondaCS6369 24012-017

Manufacturer: Winco Generators

WL12000HE-03/A 50C Package Industrial Portable Generator 24012-017  
Package includes Generator, Wheel kit, installed battery

WL12000HE-CP

The WL12000HE-CP is the workhorse of Winco's Big Dog portable generator series. The WL12000HE will save you time and money giving your company a competitive advantage over crews using other portable generators. The 15 gallon fuel tank provides 9 hours of runtime at full load so you won't have to take unscheduled breaks to refuel your industrial generator. The factory installed lifting bar makes it easy to get this generator on and off the roof while the pneumatic tires on the four wheel dolly kit make maneuvering this generator easy. The WL12000HE is the preferred portable generator in the flat top roofing industry. It is durable enough to handle the hours while providing clean power for sensitive equipment. The WL12000HE has a 60A receptacle. Honda GX630cc Engine  
512 lbs  
52 x 33 x 37

The WL12000HE-03/C 50A (this webpage) has a CS6365 50A twist lock receptacle. This package comes standard with the wheel kits and battery

[Print Brochure](#)

[Print Owner's Manual](#)

[Print Technical Specifications](#)

[Why Winco Industrial Portables?](#)

[Winco Generators Are made In The Good Old U.S.A.](#)

[American Made](#)

ELECTRICAL SPECIFICATIONS:

- Maximum Power Rating 12,000 watts
- Continuous Power Rating 10,800 watts
- AC Output Voltage 120/240 volts
- Continuous Current Rating 45 amps @240V
- Motor Starting Ability 5 HP
- Generator Type R.F.L.

## ENGINE DATA

- Make/Model Honda GX630
- Displacement 688 cc
- Rated Power (3600 rpm) 20 hp
- Low Oil Protection Standard
- Starting System Electric
- Fuel Tank Capacity 15 gallons
- Running Time-Full Load 9 hours
- Running Time-Half Load 14.5 hours
- Hour Meter Standard

## 120 VOLT RECEPTACLES

- (6) Straight Blade (NEMA 5-20R) 2-20 amp GFCI
- Twist Lock (NEMA 5-20R) 1-20 amp

## 240 VOLT RECEPTACLES

- Twist-Lock (NEMA L6-30R) 1-30 amp, GFIC

## 120/240 VOLT RECEPTACLES

- CS6365C Twist-Lock, 50 amp receptacle

## SIZE & WEIGHT

- Dimensions (LxWxH) 33x26x34 in.
- Shipping Weight 517 lbs.

## WARRANTY INFORMATION

- Generator/Engine 1 yrs/2 yrs.

## Engine

- Durable Honda GX630 commercial engine
- Cast iron cylinder sleeves
- Fuel efficient design
- Genuine Honda muffler is 2-3 dba quieter than other aftermarket designs
- Available in CARB compliant version/ EPA compliant standard
- Electric start

## Generator

- Clean power at less than 5% total harmonic distortion
- Steady voltage regulation is safe for sensitive electronics
- Heavy duty capacitors and diodes
- 100% copper windings

## Additional Features

- Large 15 gallon non-corrosive fuel tank
- Oversized full power plug
- Industrial Square D mainline circuit breaker
- Industry leading 1/60th second reaction time
- Visi-Trip indicator
- Made in USA
- Full commercial warranty
- 3 years engine
- 2 years generator

Winco Generators - Quality & Innovation since 1927.

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >

Need Help Loading & Unloading? Check Out Our Selection of Loading Ramps  
[Click Here](#)

BE ADVISED:

- Beginning December 1st, 2022, Winco has chosen to enlist an updated cancellation policy in an effort to better meet the needs of our existing partners as well as future partners.

NUMBER OF DAYS CANCELLATION REQUEST RECEIVED, FOLLOWING  
ORDER DATE  
CANCELLATION FEE

Within 0-30 days of order  
5%

Within 30-60 days of order  
10%

More than 60 days  
15%

Product Shipped  
25%

(Note: On custom orders (M-specs & C-specs); no cancellation allowed after one week of initial order date as procurement of materials has already started.)

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >



Availability: This product was added to our catalog on Wednesday 30 March, 2022

Steambrite Supply