



Model Number: 967969801

Husqvarna 967969801, External Concrete Form Vibrator, EP271 Pneumatically Operated, ENO25, GTIN 805544250504

Manufacturer: Husqvarna Equipment

Husqvarna 967969801 External Concrete Form Vibrator EP271 Pneumatically Operated 25%OFF Promo Code Applied

Limited Stock to only 6 units (July 2023).

Ships from KS location.

sku 805544250504

Efficient external concrete vibrators for all concrete mixes

Product description

The product is a concrete vibrator. The product has a pneumatically operated motor that only contains 2 moving parts. Compressed air is supplied to the product through the air valve.

An automatic lubricator can be installed as an optional equipment. The automatic lubricator is supplied by the manufacturer of the air compressor.

Intended use

The product is for professional operation only. The product removes air bubbles from wet concrete. Do not use the product for other tasks

Husqvarna offers a wide range of external concrete vibrators – all with adjustable centrifugal force. Typical applications include civil engineering sites and precast factories.

All models are made from high-quality components and materials, which helps increase the life cycle and keep maintenance costs down.

Husqvarna external vibrators provide the versatility and vibrations you need to get the job done.

Owners Manual

Great features for efficient work

Adjustable centrifugal force

Provides you with the flexibility to adjust the centrifugal force to suit the job at hand.

Quick release brackets

Quick release brackets are easier to move, so you can secure the vibrator where you need it most. This also means fewer units are required, which reduces costs.

Designed for all concrete mixes

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >

Suitable for all concrete mixes on civil engineering sites and in precast factories.
Seamless operation
A single moving part facilitates seamless operation.
Low maintenance
High quality components and materials mean no regular maintenance is required.

Please supply 42 CFM air to each unit, at 87 Psi. Trailer Air compressor not included.

Availability: This product was added to our catalog on Thursday 20 July, 2023