



Model Number: 967809101

Husqvarna 967809101, K 770 Rescue 5Hp, 12IN Blade, Cutting depth 4IN, (No Blade Included), GTIN 805544645638

Manufacturer: Husqvarna Equipment

Husqvarna K 770 Rescue 967809101 5Hp 12 Inch Blade Cutting depth 4 Inches (No Blade Included) Freight Included

Description

Our compact and lightest rescue cutter is specially developed for rescue and clearing work. The magnesium blade guard is designed to be visible in smoke and water spray, and the digital ignition system provides a reliable and quick start in any emergency situation. Used and trusted by fire services around the world.

GTIN 805544645638

Specifications

Parts List

Owners manual

Capacity

Idling speed

2700 rpm

Idling upper limit

3500 rpm

Maximum power speed

9000 rpm

Power/weight ratio

0.33 kW/kg

Output power

5 hp

Output shaft RPM, max

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >

4700 rpm

Peripheral speed, max
16000 fpm

Racing speed lower limit
9100 rpm

Dimensions

Article gross weight
12500 g

Article net weight
10600 g

Arbor diameter
0.8 in

Blade diameter, max
12 in

Blade flange diameter
4.13 in

Blade thickness, max
0.2 in

Cutting depth, max
4 in

Product size height
15.39 in

Product size length
24.33 in

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >

Product size width
8.7 in

Weight
22 lbs

Engine

Cylinder bore
2.01 in

Cylinder displacement
4.48 cu.inch

Cylinder stroke
1.42 in

Cylinders
1

Electrode gap
0.02 in

Engine cooling
Fan/Air

Max engine/motor
9300 rpm

Spark plug
NGK BPMR7A

Equipment

Starter
Manual cord with spring

Water connector
Gardena Male

Lubricants

Engine cooling
Fan/Air

Fuel consumption
470 g/kWh

Fuel tank volume
30.4 fl oz

Lubricant type (Engine)
Husqvarna 2 stroke or equiv. at 50:1

Sound and Noise

Sound power level, guaranteed (LWA)
115 dB(A)

Sound power level, measured
113 dB(A)

Sound pressure level at operators ear
101 dB(A)

Vibrations

Daily Vibration (Aeqv)
2.3 m/s²;

Daily Vibration Exposure (A8)
0.8 m/s²;

Daily Vibration Time (Time factor)
1 h

Vibrations left/front handle
2.1 m/s²;

Vibrations right/rear handle
2.3 m/s²;

Emission Data EPA

Exhaust emissions (CO average)
432.0 g/kWh

Exhaust emissions (CO FEL)
536 g/kWh

Exhaust emissions (CO_a, average)
717 g/kWh

Exhaust emissions (HC average)
49.27 g/kWh

Exhaust emissions (NO_x average)
0.94 g/kWh

Equipment: Carpet Cleaning Machines > Vacuum Cleaners > HEPA Concrete Dust Slurry Hazmat Vacuums >

Emission Data EU

Exhaust emissions (CO average)
428.16 g/kWh

Exhaust emissions (CO₂, average)
711 g/kWh

Exhaust emissions (HC average)
51.36 g/kWh

Exhaust emissions (NO_x average)
0.94 g/kWh

Packaging

Packaging length
700 mm

Packaging width
250 mm

Packaging height
430 mm

Optional

Husqvarna Vari-Cut 12 Inch Blade 542751358 Cutting Concrete Brick Roof
Tile Flint Granite Marble Natural Stone Iron

Availability: This product was added to our catalog on Monday 07 August, 2023